

according to 1907/2006/EC, Article 31

Page 1/7

Printing date 19.09.2013 Revision: 19.09.2013 Version number 1

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics
- Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the preparation Polishing agent/ Burnishing compound
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstr. 22

42655 SOLINGEN

Germany

Tel.: +49 (0)212 - 2718-0 Fax: +49 (0)212 - 208795

www.autosol.de www.dursol.de

· Further information obtainable from:

Abteilung Produktsicherheit labor@autosol.de

· Emergency telephone number:

+49 (0)212 - 2718-0 8.00 - 16.00 h

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

· Special labelling of certain preparations:

Safety data sheet available for professional user on request.

- · Additional information: Keep out of reach of children.
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Page 2/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 1)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 8008-20-6	Kerosine (petroleum)	25-50%
EINECS: 232-366-4	Xn R65	
	♦ Asp. Tox. 1, H304	
CAS: 1332-58-7	Kaolin	10-25%
	substance with a Community workplace exposure limit	
CAS: 1344-28-1	aluminium oxide	1-10%
EINECS: 215-691-6	substance with a Community workplace exposure limit	
CAS: 100-37-8	2-diethylaminoethanol	1-10%
EINECS: 202-845-2	C R34; Xn R20/21/22	
	R10	
	 Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Acute Tox. 4, H302; STOT SE 3, H335 	
	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; STOT SE 3, H335	

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Page 3/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 2)

· Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Pick up mechanically.
- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

No special measures required.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · Storage class: 13
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

1332-58-7 Kaolin

WEL Long-term value: 2 mg/m³

1344-28-1 aluminium oxide

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Avoid skin contact with the liquefied material.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Page 4/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 3)

The usual precautionary measures are to be adhered to when handling chemicals.

- Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:

Solvent resistant gloves

Alkaline resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

9 Physical and chemical properties

Information on basic physical and	chemical properties	
General Information		
· Appearance: Form:	Pasty	
Colour:	White	
Odour:	Characteristic	
Odour threshold:	Not determined.	
· pH-value at 20 °C:	8.5	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.	
· Flash point:	> 100 °C	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower:	Not determined.	

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Page 5/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 4

		(Contd. of page 2
Upper:	Not determined.	
· Vapour pressure:	Not applicable.	
· Density at 20 °C:	1.1 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Insoluble.	
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Other information	No further relevant information available	

10 Stability and reactivity

- · Reactivity
- **Chemical stability**
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50	· LD/LC50 values relevant for classification:		
8008-20-6	8008-20-6 Kerosine (petroleum)		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rabbit)	
100-37-8	100-37-8 2-diethylaminoethanol		
Oral	LD50	1300 mg/kg (rat)	
Inhalative	LC50 (4 h)	5 mg/l (mouse)	

- Primary irritant effect:
- on the skin: No irritant effect.on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Page 6/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 5)

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	

Contd. on page 7)



according to 1907/2006/EC, Article 31

Page 7/7
Printing date 19.09.2013
Revision: 19.09.2013
Version number 1

Trade name: AUTOSOL® M1 Cleaning Polish for Chrome Plated Plastics

(Contd. of page 6)

· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	k II of Not applicable.

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R34 Causes burns.

R65 Harmful: may cause lung damage if swallowed.

Department issuing MSDS:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstraße 22 42655 Solingen

Germany

Abteilung F&E / Produktsicherheit

· Contact: labor@autosol.de