

10K BOOST MASS AIR FLOW SENSOR CLEANER

Page: 1

Compilation date: 14/04/2015

Revision date: 07/02/2017

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

# Product name: 10K BOOST MASS AIR FLOW SENSOR CLEANER

Product code: 1442

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Granville Oil & Chemicals Ltd.
---------------	--------------------------------

Unit 29 Goldthorpe Industrial Estate

Goldthorpe

Rotherham

South Yorkshire

S63 9BL

United Kingdom

Tel: +44 (0)1709 890099

Fax: +44 (0)1709 891121

Email: technical@granvilleoil.com

#### 1.4. Emergency telephone number

Emergency tel: +44 (0)1709 890099

(office hours only)

#### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; -: H229

**Most important adverse effects:** Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation.

#### 2.2. Label elements

Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
Hazard pictograms:	GHS02: Flame

GHS07: Exclamation mark



#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

	-
Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of water/soap.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
2.2 Other hererde	

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

# Hazardous ingredients:

#### XYLENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	30-50%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

# PROPANE

200-827-9 74		Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
--------------	--	--	-------------------------------------	--------

#### ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	10-30%
			STOT SE 3: H336; -: EUH066	

# DIACETONE ALCOHOL

204-626-7	123-42-2	-	Eye Irrit. 2: H319	1-10%

# BUTANE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		

# 10K BOOST MASS AIR FLOW SENSOR CLEANER

ISOBUTANE						
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%		
METHANOL						
200-659-6	67-56-1	-	1-10%			
Section 4: First a	aid measures					
4.1. Description	n of first aid me	asures				
	Skin contact:	Remove all contaminated clothes and	d footwear immediately unless stuck to skin. Was	sh		
		immediately with plenty of soap and				
	Eye contact:	Bathe the eye with running water for				
	Ingestion:	Do not induce vomiting. Wash out me	outh with water. Consult a doctor.			
	Inhalation:	Move to fresh air in case of accidenta	al inhalation of vapours.			
4.2. Most impo	rtant symptoms	and effects, both acute and delaye	d			
	Skin contact: There may be irritation and redness at the site of contact.					
		There may be irritation and redness.				
	<b>Ingestion:</b> There may be soreness and redness of the mouth and throat.					
	<b>Inhalation:</b> There may be irritation of the throat with a feeling of tightness in the chest. Exposure may					
	cause coughing or wheezing.					
<b>Delayed / immediate effects:</b> Immediate effects can be expected after short-term exposure.						
4.3. Indication of any immediate medical attention and special treatment needed						
Immediate / spe	cial treatment:	Eye bathing equipment should be available	ailable on the premises.			
Section 5: Fire-fi	ghting measu	res				
5.1. Extinguishi	ing media					
Extingu	uishing media:	Suitable extinguishing media for the	surrounding fire should be used.			
5.2. Special haz	ards arising fro	om the substance or mixture				
Expo	osure hazards:	Extremely flammable. In combustion	emits toxic fumes. Forms explosive air-vapour			
		mixture. Vapour may travel considera	able distance to source of ignition and flash back.			
5.3. Advice for	fire-fighters					
Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.						
Section 6: Accid	ental release r	neasures				

#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

6.1. Personal precautions, protective equipment and emergency procedures Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind. 6.2. Environmental precautions Environmental precautions: Do not discharge into drains or rivers. 6.3. Methods and material for containment and cleaning up Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. 6.4. Reference to other sections Reference to other sections: Refer to section 8 of SDS. Section 7: Handling and storage 7.1. Precautions for safe handling Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance. 7.2. Conditions for safe storage, including any incompatibilities Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight.

**Suitable packaging:** Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

# Hazardous ingredients:

# XYLENE

# Workplace exposure limits:

# State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL UK 220 mg/m3 441 mg/m3

Respirable dust

#### PROPANE

UK 1800 mg/m3 7200 mg/m3	-	-
--------------------------	---	---

# [cont...]

# 10K BOOST MASS AIR FLOW SENSOR CLEANER

**Page:** 5

ACETONE				
UK	1210 mg/m3	3620 mg/m3	-	-
BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	-
METHANOL				
UK	266 mg/m3	333 mg/m3	-	-
-	· · · · · · · · · · · · · · · · · · ·			

# **DNEL/PNEC** Values

# Hazardous ingredients:

#### XYLENE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	442 mg/m3	Workers	Local
DNEL	Inhalation	180 mg/kg/day	Workers	Systemic
DNEL	Dermal	3182 mg/kg/day	Workers	Systemic
PNEC	Fresh water	0.327 mg/l	-	-
PNEC	Fresh water sediments	12.46 mg/kg	-	-
PNEC	Marine sediments	12.46 mg/kg	-	-
PNEC	Soil (agricultural)	2.31 mg/kg	-	-

# METHANOL

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	40 mg/kg/day	Workers	Systemic
DNEL	Inhalation	260 mg/m3	Workers	Systemic
DNEL	Dermal	40 mg/kg/day	Workers	Local
DNEL	Inhalation	260 mg/m3	Workers	Local
DNEL	Dermal	8mg/kg/day	Consumers	Systemic
DNEL	Inhalation	50 mg/m3	Consumers	Systemic
DNEL	Oral	8 mg/kg/day	Consumers	Local

# 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical	
	equipment are not a source of ignition.	
Respiratory protection:	Respiratory protection not required.	
Hand protection:	Protective gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	
Environmental:	Prevent from entering in public sewers or the immediate environment.	

#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

**Page:** 6

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

#### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

#### Page: 7

#### METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

#### **Relevant hazards for product:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

#### Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

#### Hazardous ingredients:

#### ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300 mg/l	
--------------------------------	------	-----------	--

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

Recovery operations: Not applicable.

# **NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Marine pollutant: No

# Section 14: Transport information

# 14.1. UN number

UN number: UN1950

#### 14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

# Section 16: Other information

#### Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H226: Flammable liquid and vapour.
	H229: Pressurised container: May burst if heated

#### 10K BOOST MASS AIR FLOW SENSOR CLEANER

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.