Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK) SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Castrol EDGE Turbo Diesel 5W-40 (EU)
468382-BE02
468382
Liquid.
s of the substance or mixture and uses advised against
Engine Oils.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.
of the safety data sheet
Castrol (UK) Ltd
Wakefield House
Pipers Way Swindon
Wiltshire SN3 1RE
MSDSadvice@bp.com
umber
Carechem:+44 (0) 1235 239 670 (24 hours)

2.1 Classification of the substance or mixture

 Product definition
 Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Not classified.

Classification according to Directive 1999/45/EC [DPD]

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments. See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Supplemental label elements	Safety data sheet available on request.
Special packaging requireme	nts
	nts Not applicable.

2.3 Other hazards

Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 46	68382-BE02	Page: 1/10
Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom	Language	ENGLISH

SECTION 2: Hazards identification

Other hazards which do not result in classification	Defatting to the skin. USED ENGINE OILS
	Used engine oil may contain hazardous components which have the potential to cause skin cancer.
	See Toxicological Information, section 11 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

Substance/mixture

Chemically modified base oil Proprietary performance additives.

Mixture

		Classification			
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1	>=5 - <10	Not classified.	Asp. Tox. 1, H304	[1]
Calcium long chain alkyl salicylate	Index: 649-483-00-5 EC: 281-018-8 CAS: 83846-43-9	>=1 - <5	Not classified.	Aquatic Chronic 3, H41	2 [1]

See Section 16 for the full text of the H statements declared above.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	easures
Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

	Notes to physician Treatment should in general	be symptomatic and directed to relieving any effects.
--	--	---

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the	In a fire or if heated, a pressure increase will occur and the container may burst.
substance or mixture	

Product name Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 468382-	BE02	Page: 2/10
Version 1 Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 5: Firefighting measures

Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire- fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	containment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other	See Section 1 for emergency contact information.
sections	See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment.
	See Section 12 for environmental precautions.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.
Not suitable	Prolonged exposure to elevated temperature
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

Γ	Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 4683	382-BE02	Page: 3/10	
	Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.

Occupational exposure limits

No exposure limit value known.

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Derived No Effect Level	
No DNELs/DMELs available.	
Predicted No Effect Concentra	<u>ation</u>
No PNECs available	
2 Exposure controls	
Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
ndividual protection measure	-
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should

Eye/face protection Skin protection Hand protection

General Information:

of the working conditions.

Safety glasses with side shields.

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

therefore be chosen in consultation with the supplier/manufacturer and with a full assessment

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves. **Breakthrough time:**

Breakthrough time data are generated by glove manufacturers under laboratory test conditions

Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 46838	2-BE02	Page: 4/10
Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 8: Exposure controls/personal protection

	and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:
	Continuous contact:
	Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves
	can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.
	Short-term / splash protection:
	Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.
	Glove Thickness:
	For general applications, we recommend gloves with a thickness typically greater than 0.35 mm
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.
Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular
	basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
SECTION 9: Physical	and chemical properties
9.1 Information on basic physic	cal and chemical properties
Appearance	
Physical state	Liquid.
Physical state	
Colour	Amber. [Light]
	Amber. [Light] Not available.
Colour	
Colour Odour	Not available.

Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 468382	-BE02	Page: 5/10
Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 9: Physical and chemical properties

Initial boiling point and boiling	Not available.
range	40.80
Pour point	-48 °C
Flash point	Closed cup: 210°C (410°F) [Pensky-Martens.] [Product does not sustain combustion.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	848 kg/m³ (0.848 g/cm³) at 15°C
Solubility(ies)	insoluble in water.
Partition coefficient: n-octanol/ water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 82 mm²/s (82 cSt) at 40°C Kinematic: 13.9 mm²/s (13.9 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

	Route	ATE value
Not available.		
nformation on the likely outes of exposure	Routes of entry anticipated: Dermal, Inhalation	n.
otential acute health effects		
Inhalation	Vapour inhalation under ambient conditions is pressure.	not normally a problem due to low vapour
Ingestion	No known significant effects or critical hazards	S.
Skin contact	Defatting to the skin. May cause skin dryness	and irritation.
Eye contact	No known significant effects or critical hazards	S.

Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 468382-	BE02	Page: 6/10
Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 11: Toxicological information

Inhalation	No specific data.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.
Delayed and immediate effe	ects and also chronic effects from short and long term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Potential chronic health eff	<u>ects</u>
General	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity	
Environmental hazards	1

ental hazards	Not classified as dangerous
---------------	-----------------------------

12.2 Persistence and degradability

Not expected to be rapidly degradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.
12.5 Results of PBT and vPvB a	assessment
PBT	Not applicable.
vPvB	Not applicable.

12.6 Other adverse effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal considerations

13.1 Waste treatment metho	ds
Product	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Hazardous waste	Yes.
European waste catalogu	<u>e (EWC)</u>
Waste code	Waste designation

Wa	ste code	Waste designation				
13 02 05*		mineral-based non-chlorinated engine, gear and lubricating oils				
Product nam	e Castrol EDGE T	urbo Diesel 5W-40 (EU)		Product code	468382-BE02	Page: 7/10
Version 1	Date of issue	11 February 2014	Format	United Kingdom (UK) (United Kingdo	Language	ENGLISH

SECTION 13: Disposal considerations

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ	
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.2 UN proper shipping name	-	-	-	-	
14.3 Transport hazard class(es)	-	-	-	-	
14.4 Packing group	-	-	-	-	
14.5 Environmental hazards	No.	No.	No.	No.	
Additional information	-	-	-	-	

14.6 Special precautions for Not available. user

SECTION 15: Regulatory information

15.1 Safety, health and environ	mental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2	2006 (REACH)
Annex XIV - List of substanc	es subject to authorisation
Substances of very high co	ncern
None of the components are	e listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Other regulations	
REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States inventory (TSCA 8b)	All components are listed or exempted.
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	At least one component is not listed.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.

 Product name
 Castrol EDGE Turbo Diesel 5W-40 (EU)
 Product code 468382-BE02
 Page: 8/10

 Version 1
 Date of issue 11 February 2014
 Format
 United Language Kingdom (UK) (UK) (United Kingdom)
 ENGLISH

SECTION 15: Regulatory information

15.2 Chemical Safety This product contains substances for which Chemical Safety Assessments are still Assessment Assessment	required.

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by					
	Inland Waterway					
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by					
	Road ATE - Acute Toxicity Estimate					
	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor					
	CAS = Chemical Abstracts Service					
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]					
	CSA = Chemical Safety Assessment					
	CSR = Chemical Safety Report					
	DMEL = Derived Minimal Effect Level					
	DNEL = Derived No Effect Level DPD = Dangerous Preparations Directive [1999/45/EC]					
	DSD = Dangerous Substan					
		tory of Existing Commercial chemical Substances				
	ES = Exposure Scenario					
	EUH statement = CLP-spec	cific Hazard statement				
	EWC = European Waste Catalogue					
		d System of Classification and Labelling of Chemicals				
	IATA = International Air Transport Association					
	IBC = Intermediate Bulk Container					
	IMDG = International Maritime Dangerous Goods					
	LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as					
	modified by the Protocol of 1978. ("Marpol" = marine pollution)					
	OECD = Organisation for Economic Co-operation and Development					
	PBT = Persistent, Bioaccumulative and Toxic					
	PNEC = Predicted No Effect Concentration					
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail					
	RRN = REACH Registration					
	SADT = Self-Accelerating L SVHC = Substances of Ver	Decomposition Temperature				
	STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure					
	TWA = Time weighted average					
	UN = United Nations					
	UVCB = Complex hydrocarbon substance					
	VOC = Volatile Organic Compound					
	vPvB = Very Persistent and	-				
Full text of abbreviated H statements	H304 H412	May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.				
Full text of classifications [CLP/GHS]	Aquatic Chronic 3, H412 Asp. Tox. 1, H304	LONG-TERM AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1				
Full text of abbreviated R phrases	Not applicable.					
Full text of classifications [DSD/DPD]	Not applicable.					
History						
Date of issue/ Date of revision	11/02/2014.					
Date of previous issue	No previous validation.					
Prepared by	Product Stewardship					

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP

Product name Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 468382-BE02		Page: 9/10	
Version 1	Date of issue 11 February 2014		United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 16: Other information

Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Castrol EDGE Turbo Diesel 5W-40 (EU)		Product code 46838	2-BE02	Page: 10/10
Version 1	Date of issue 11 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH