

1. Identification of the substance/preparation and company/undertaking

Product name	Castrol Motorcycle Coolant
SDS no.	52742
Use of the substance/preparation	Coolant and antifreeze. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE
EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 208 762 8322 (24 hours)
E-mail address	MSDSadvice@bp.com

2. Hazards identification

This preparation is classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Human health hazards Harmful if swallowed.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

3. Composition/information on ingredients

Ethylene glycol Corrosion inhibitor.

Chemical name	CAS no.	%	EINECS / ELINCS.	Classification	
Ethylene glycol; ethanediol	107-21-1	20 - 50	203-473-3	Xn; R22	[1] [2]

See section 16 for the full text of the R-phrases declared above

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. First-aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Get medical attention urgently informing the doctor that a product containing ethylene glycol has been ingested and specific treatment may be required (see Advice to physicians). If hospital facilities or medical assistance are NOT immediately available: If contamination of the mouth occurs, wash out thoroughly with water. If larger amounts are swallowed and hospital facilities or medical assistance are not immediately available, induce vomiting if the casualty is fully conscious. Never attempt to induce vomiting in an unconscious or semi-conscious patient. Transport casualty together with the product container, its label or the safety data sheet urgently to hospital. Inform the doctor that a product containing ethylene glycol has been ingested.
Notes to physician	Gastric lavage is indicated if significant quantities have been ingested in the previous 4 hours. The metabolism of the glycol to oxalic acid may be delayed by the intravenous administration of ethanol (give as a 5% solution in physiological saline to maintain a blood level of 1-2mg/ml). This has been shown to be an effective antidote provided treatment is started within about 6 hours of exposure. The glycol may be removed by dialysis but oxalates are not readily removed.

Product name	Castrol Motorcycle Coolant	Product code	52742-IT13	Page:	1/5
Date of issue	18 September 2009	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH (ENGLISH)

5. Fire-fighting measures

Extinguishing media

Suitable

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray. Alcohol resistant foam

Not suitable

Do not use water jet.

Hazardous decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Unusual fire/explosion hazards

This material is not explosive as defined by established regulatory criteria.

Special fire-fighting procedures

None identified.

Protection of fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Wash thoroughly after handling. Avoid contact with eyes, skin and clothing.

Storage

Keep out of the reach of children.
Store in original container; DO NOT DECANT.
Do not remove warning labels from containers. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Not suitable

Prolonged exposure to elevated temperature

8. Exposure controls/personal protection

Ingredient name

Ethylene glycol; ethanediol

Occupational exposure limits

EH40/2005 WELs (United Kingdom (UK)). Absorbed through skin.

STEL: 104 mg/m³ 15 minute(s). Issued/Revised: 4/2005 Form: Vapour
STEL: 40 ppm 15 minute(s). Issued/Revised: 4/2005 Form: Vapour
TWA: 52 mg/m³ 8 hour(s). Issued/Revised: 4/2005 Form: Vapour
TWA: 20 ppm 8 hour(s). Issued/Revised: 4/2005 Form: Vapour
TWA: 10 mg/m³ 8 hour(s). Issued/Revised: 12/2001 Form: Particulate

ACGIH TLVs

Ethylene glycol; ethanediol

ACGIH TLV (United States).

C: 100 mg/m³ Issued/Revised: 5/1995 Form: Aerosol

For information and guidance, the ACGIH values are included. For further information on these please consult your supplier.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Exposure controls

Occupational exposure controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.

All chemicals should be assessed for their risks to health and appropriate control measures put in place to prevent or adequately control exposure. A hierarchy of control measures exists (e.g. elimination, substitution, general ventilation, containment, systems of work, changing the process or activity) that must be considered before use of personal protective equipment. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Product name	Castrol Motorcycle Coolant	Product code	52742-IT13	Page:	2/5
Date of issue	18 September 2009	Format	United Kingdom (UK)	Language	ENGLISH
			(United Kingdom)		(ENGLISH)

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protective equipment

Respiratory protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn.

Air-filtering respirators, also called air-purifying respirators, will not be adequate under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required.

Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves.

Recommended: Butyl gloves. Neoprene gloves.

Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Eye protection

Safety glasses with side shields.

Skin and body

Use of protective clothing is good industrial practice.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

9 . Physical and chemical properties

General information

Appearance

Physical state Liquid.

Colour Blue.

Odour Oily.

Important health, safety and environmental information

pH

Boiling point / range 108°C (226.4°F)

Pour point -30 °C

Density 1052 to 1058 kg/m³ (1.052 to 1.058 g/cm³) at 20°C

Solubility Soluble in water.

Partition coefficient <1

(LogKow)

10 . Stability and reactivity

Stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid No specific data.

Materials to avoid Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products Combustion products may include the following:
carbon oxides

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Acute toxicity Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.

Harmful if swallowed.

At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Product name Castrol Motorcycle Coolant

Product code 52742-IT13

Page: 3/5

Date of issue 18 September 2009

Format United Kingdom
(UK)

Language ENGLISH

(United Kingdom)

(ENGLISH)

Chronic toxicity	<input checked="" type="checkbox"/> No known significant effects or critical hazards.
Chronic effects	
Effects and symptoms	
Eyes	No significant health hazards identified.
Skin	No significant health hazards identified.
Inhalation	No significant health hazards identified.
Ingestion	Harmful if swallowed.

12 . Ecological information

Persistence/degradability	Inherently biodegradable
Mobility	<input checked="" type="checkbox"/> Spillages may penetrate the soil causing ground water contamination.
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
Environmental hazards	Not classified as dangerous.
Other ecological information	Miscible in water.

13 . Disposal considerations

Disposal considerations / Waste information	<input checked="" type="checkbox"/> The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.
Unused product	
European waste catalogue (EWC)	16 01 14* antifreeze fluids containing dangerous substances However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

14 . Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

15 . Regulatory information

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted.

Label requirements

Hazard symbol or symbols



Harmful

Indication of danger	
Risk phrases	R22- Harmful if swallowed.
Safety phrases	S2- Keep out of the reach of children. S46- If swallowed, seek medical advice immediately and show this container or label.
Contains	<input checked="" type="checkbox"/> Ethylene glycol; ethanediol
Tactile warning of danger	<input checked="" type="checkbox"/> Yes, applicable.
Other regulations	
Europe inventory	<input checked="" type="checkbox"/> All components are listed or exempted.
United States inventory (TSCA 8b)	<input checked="" type="checkbox"/> Not determined.
Australia inventory (AICS)	<input checked="" type="checkbox"/> Not determined.
Canada inventory	<input checked="" type="checkbox"/> Not determined.
China inventory (IECSC)	<input checked="" type="checkbox"/> Not determined.
Japan inventory (ENCS)	<input checked="" type="checkbox"/> Not determined.
Korea inventory (KECI)	<input checked="" type="checkbox"/> Not determined.
Philippines inventory (PICCS)	<input checked="" type="checkbox"/> Not determined.

Product name Castrol Motorcycle Coolant	Product code <input checked="" type="checkbox"/> 52742-IT13	Page: 4/5
Date of issue 18 September 2009	Format United Kingdom (UK) (United Kingdom)	Language ENGLISH (ENGLISH)

16 . Other information

Full text of R-phrases referred to in sections 2 and 3  22- Harmful if swallowed.


History

Date of issue/ Date of revision 18/09/2009.

Date of previous issue 11/05/2007.

Prepared by Product Stewardship

Notice to reader

 Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name Castrol Motorcycle Coolant	Product code  52742-IT13	Page: 5/5
Date of issue 18 September 2009	Format United Kingdom (UK)	Language ENGLISH
	(United Kingdom)	(ENGLISH)