



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** **AUTOSOL® Aluminium Polish**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Maintenance product
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - Dursol-Fabrik Otto Durst GmbH & Co. KG
 - Martinstr. 22
 - 42655 SOLINGEN
 - Germany
 - Tel.: +49 (0)212 - 2718-0
 - Fax: +49 (0)212 - 208795
 - www.autosol.de www.dursol.de
- **Further information obtainable from:**
 - Abteilung Produktsicherheit
 - labor@autosol.de
- **Emergency telephone number:**
 - +49 (0)212 - 2718-0
 - 8.00 - 16.00 h

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R38: Irritating to skin.
R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 1)

Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xi Irritant

Risk phrases:

38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

2 Keep out of the reach of children.

13 Keep away from food, drink and animal feedingstuffs.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

36 Wear suitable protective clothing.

46 If swallowed, seek medical advice immediately and show this container or label.

52 Not recommended for interior use on large surface areas.

60 This material and its container must be disposed of as hazardous waste.

Additional information: Keep out of reach of children.**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn R65; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H336	10-25%
--------------------------------------	---	--------

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 2)

CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) ☒ Xn R65 ☠ Asp. Tox. 1, H304; Aquatic Chronic 3, H412	10-25%
CAS: 100-37-8 EINECS: 202-845-2	2-diethylaminoethanol ☠ C R34; ☒ Xn R20/21/22 R10 ☠ Flam. Liq. 3, H226; ☠ Acute Tox. 3, H311; Acute Tox. 3, H331; ☠ Skin Corr. 1B, H314; ☠ Acute Tox. 4, H302; STOT SE 3, H335	1-10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol ☠ F R11 ☠ Flam. Liq. 2, H225	1-10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.**· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** None.**· Storage class:** 10**· Specific end use(s):** No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.**· Control parameters****· Ingredients with limit values that require monitoring at the workplace:****64-17-5 ethanol**WEL | Long-term value: 1920 mg/m³, 1000 ppm**· Additional information:** The lists valid during the making were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Rubber gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 4)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.5 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

· **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Pasty

Colour: Grey

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C

· **Flash point:** > 100 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** 1.048 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 5)

- | | |
|----------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

8008-20-6 Kerosine (petroleum)

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rabbit)

100-37-8 2-diethylaminoethanol

Oral	LD50	1300 mg/kg (rat)
Inhalative	LC50 (4 h)	5 mg/l (mouse)

64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat) (OECD 401 (Acute Oral Toxicity))
Dermal	LD50	>2000 mg/kg (rabbit) (OECD 402 (Acute Dermal Toxicity))
Inhalative	LC50 (4 h)	117-125 mg/l (rat) (OECD 403 (Acute Inhalation Toxicity))

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 6)

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

64-17-5 ethanol

LC50 (48 h) | 12340 mg/l (daphnia)

LC50 (96 h) | 13000 mg/l (fish)

- **Persistence and degradability**

64-17-5 ethanol

BCF | 3.2 mg/l (Bioconcentrationfactor)

log POW | -0.32 (log POW)

- **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **ADR, IMDG, IATA**

UN1993

- **ADN**

Void

- **UN proper shipping name**

- **ADR, ADN**

Void

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 7)

· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light)
· Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· ADN/R Class:	Void
· Packing group	
· ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D/E
· UN "Model Regulation":	-

15 Regulatory information

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2014

Revision: 11.03.2014

Version number 1

Trade name: AUTOSOL® Aluminium Polish

(Contd. of page 8)

H412	Harmful to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

Dursol-Fabrik Otto Durst GmbH & Co. KG
Martinstraße 22
42655 Solingen
Germany

Abteilung F&E / Produktsicherheit

· **Contact:** labor@autosol.de

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent