# SAFETY DATA SHEET



### 1. Identification of the substance/preparation and company/undertaking

Product name	Castrol TWS Motorsport 10W-60
SDS no.	<u>4</u> 52649
Use of the substance/preparation	Mutomotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE
EMERGENCY TELEPHONE	
NUMBER	Carechem: +44 (0) 208 762 8322 (24 hours)
E-mail address	MSDSadvice@bp.com

### 2. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Additional hazards

SED ENGINE OILS

Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

### 3. Composition/information on ingredients

Synthetic base stock. Proprietary performance additives.

Chemical name	CAS no.	%	EINECS / ELINCS.	Classificatio	on
Solyolefin polyamine succinimide, polyol	147880-09-9	1 - 5		R53	[1]
See section 16 for the full text of the R-phrases decl [1] Substance classified with a health or environmental haza [2] Substance with a workplace exposure limit [3] PBT-substance [4] vPvB-substance Occupational exposure limits, if available, are listed	rd				
4. First-aid measures					

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.

### 5. Fire-fighting measures

Extinguishing media	
Suitable	🗖 case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	🗭 not use water jet.
Hazardous decomposition products	Composition products may include the following materials: carbon dioxide carbon monoxide
Unusual fire/explosion hazards	None identified.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fre-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Product name	Sastrol TWS Motorsport 10W-60	Product code 452	649-DE01	Page: 1/5
Version 1	Date of issue 8 December 2008	Format United Kingdom (UK)	Language	ENGLISH
		(United Kingdom)		(ENGLISH)

### 6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	woid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

# 7. Handling and storage

Handling	Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.

#### \_ . 41 \_ 4... +

8. Exposure controls	s/personal protection
Ingredient name	Occupational exposure limits
Sase oil - unspecified	<b>EH40 (United Kingdom (UK)).</b> TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Oil mist, mineral STEL: 10 mg/m <sup>3</sup> 15 minute(s). Form: Oil mist, mineral
	nponents may be shown in this section, other components may be present in any mist, vapour or dust DELs may not be applicable to the product as a whole and are provided for guidance only.
Exposure controls	
Occupational exposure controls	Frovide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
	All chemicals should be assessed for their risks to health and appropriate control measures put in place to prevent or adequately control exposure. A hierarchy of control measures exists (e.g. elimination, substitution, general ventilation, containment, systems of work, changing the process or activity) that must be considered before use of personal protective equipment. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.
	The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Hygiene measures	$\overline{W}$ ash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Personal protective equipment	
Respiratory protection	Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn.
	Air-filtering respirators, also called air-purifying respirators, will not be adequate under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required.
	Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves.
	Recommended: nitrile gloves
	Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.
Eye protection	Safety glasses with side shields.
Skin and body	Use of protective clothing is good industrial practice.
	Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

(ENGLISH)

# 9. Physical and chemical properties

General information	
Appearance	
Physical state	Liquid.
Colour	Brown.
Odour	Øily.
Important health, safety and envir	onmental information
Flash point	Øosed cup: 200°C (392°F) [Pensky-Martens.]
Viscosity	Kinematic: 24.5 mm²/s (24.5 cSt) at 100°C
Pour point	<mark>-</mark> 51 °C
Density	₿65 kg/m³ (0.865 g/cm³) at 15°C
Partition coefficient (LogKow)	▶3

# 10. Stability and reactivity

Stability Possibility of hazardous reactions	IF product is stable. If a product is stable. If a product is stable. If a product is stable.
Conditions to avoid	No specific data.
Materials to avoid	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Combustion products may include the following: carbon oxides
	Moder normal conditions of storage and use, hazardous decomposition products should not be produced.

# 11. Toxicological information

-	
Acute toxicity	Inlikely to cause more than transient stinging or redness if accidental eye contact occurs.
	Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.
	Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
	At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Chronic toxicity	
Chronic effects	Frolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Other chronic texicity date	
Other chronic toxicity data	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Effects and symptoms	Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be
	Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be
Effects and symptoms	Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Effects and symptoms Eyes	Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

### 12. Ecological information

Persistence/degradability	Inherently biodegradable
Mobility	Spillages may penetrate the soil causing ground water contamination.
Bioaccumulative potential Environmental hazards Other ecological information	This product is not expected to bioaccumulate through food chains in the environment. Not classified as dangerous. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

### 13. Disposal considerations

**Disposal considerations** / Waste information

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **Unused product**

European waste catalogue (EWC)

1/3 02 06\* synthetic engine, gear and lubricating oils However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

### 14. Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

### 15. Regulatory information

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted. Label requirements

Risk phrases	This product is not classified according to EU legislation.
Additional warning phrases	contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction. Safety data sheet available for professional user on request.
Other regulations	
Europe inventory	M components are listed or exempted.
United States inventory (TSCA 8b)	M components are listed or exempted.
Australia inventory (AICS)	Al components are listed or exempted.
Canada inventory	At least one component is not listed.
China inventory (IECSC)	A components are listed or exempted.
Japan inventory (ENCS)	A components are listed or exempted.
Korea inventory (KECI)	M components are listed or exempted.
Philippines inventory (PICCS)	Al components are listed or exempted.

### 16. Other information

Full text of R-phrases referred to in sections 2 and 3	₱53- May cause long-term adverse effects in the aquatic environment.
History	
Date of issue/ Date of revision	08/12/2008.
Date of previous issue	23/01/2004.
Prepared by	Product Stewardship Group
Notice to reader	

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

**Product name** Version 1

Product code 452649-DE01 Page: 4/5 Format United Kingdom Language ENGLISH (UK) (United Kingdom)

(ENGLISH)

Product name Version 1