

1. Identification of the substance/preparation and company/undertaking

Product name	Castrol Power 1 TTS 2T
SDS no.	465276
Use of the substance/preparation	Lubricant for two-stroke engines. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Synonyms	Castrol PowerRS TTS 2T
Supplier	Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE
EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 208 762 8322 (24 hours)
E-mail address	MSDSadvice@bp.com

2. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Additional hazards NOTE: Product diluted with petrol must be handled with the same precautions used for petrol. Before mixing, the Safety Data Sheet for petrol should be consulted for any precautionary measures necessary.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

3. Composition/information on ingredients

Synthetic base stock. Proprietary performance additives.

Chemical name	CAS no.	%	EINECS / ELINCS.	Classification	
Low boiling point hydrogen treated naphtha	64742-48-9	20 - 50	265-150-3	Xn; R65 R66	[1]

See section 16 for the full text of the R-phrases declared above

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. First-aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.

5. Fire-fighting measures

Extinguishing media	
Suitable	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Hazardous decomposition products	Decomposition products may include the following materials: carbon oxides nitrogen oxides
Unusual fire/explosion hazards	None identified.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Product name	Castrol Power 1 TTS 2T	Product code	465276-IT01	Page:	1/5
Version	4	Date of issue	25 March 2009	Format	United Kingdom (UK) (United Kingdom)
				Language	ENGLISH (ENGLISH)

6 . Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

Handling	Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Keep out of the reach of children.
Not suitable	Prolonged exposure to elevated temperature.

8 . Exposure controls/personal protection

Ingredient name	Occupational exposure limits
Low boiling point hydrogen treated naphtha	EH40 (United Kingdom (UK)). TWA: 1200 mg/m ³ 8 hour(s).
Base oil - unspecified	EH40 (United Kingdom (UK)). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral

ACGIH TLVs

Base oil - unspecified	ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral
------------------------	--

For information and guidance, the ACGIH values are included. For further information on these please consult your supplier.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Exposure controls

Occupational exposure controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.

All chemicals should be assessed for their risks to health and appropriate control measures put in place to prevent or adequately control exposure. A hierarchy of control measures exists (e.g. elimination, substitution, general ventilation, containment, systems of work, changing the process or activity) that must be considered before use of personal protective equipment. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protective equipment

Respiratory protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn.

Air-filtering respirators, also called air-purifying respirators, will not be adequate under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required.

Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Product name	Castrol Power 1 TTS 2T	Product code	465276-IT01	Page:	2/5
Version	4	Date of issue	25 March 2009	Format United Kingdom (UK)	Language ENGLISH (ENGLISH)

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves.

Recommended: nitrile gloves

Eye protection

Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Skin and body

Safety glasses with side shields.

Use of protective clothing is good industrial practice.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

9 . Physical and chemical properties

General information

Appearance

Physical state Liquid.

Colour Red.

Odour Oily.

Important health, safety and environmental information

Flash point Closed cup: 73°C (163.4°F) [Pensky-Martens.]

Viscosity Kinematic: 43 mm²/s (43 cSt) at 40°C
Kinematic: 7.6 mm²/s (7.6 cSt) at 100°C

Pour point -51 °C

Density 875 kg/m³ (0.875 g/cm³) at 15°C

Solubility insoluble in water.

Partition coefficient (LogKow) >3

10 . Stability and reactivity

Stability The product is stable. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Keep away from heat, sparks and flame.

Materials to avoid Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products Combustion products may include the following:
carbon oxides
nitrogen oxides

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Acute toxicity Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.

Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Chronic toxicity

Chronic effects Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Effects and symptoms

Eyes No significant health hazards identified.

Skin No significant health hazards identified.

Inhalation No significant health hazards identified.

Ingestion No significant health hazards identified.

12 . Ecological information

Persistence/degradability Not readily biodegradable.

Mobility Spillages may penetrate the soil causing ground water contamination.

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Environmental hazards Not classified as dangerous.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Product name	Castrol Power 1 TTS 2T	Product code	465276-IT01	Page:	3/5
Version	4	Date of issue	25 March 2009	Format	United Kingdom (UK)
				Language	ENGLISH (ENGLISH)

13 . Disposal considerations

Disposal considerations / Waste information

The generation of waste should be avoided or minimised wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Unused product

European waste catalogue (EWC)

13 02 06* synthetic engine, gear and lubricating oils
However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

14 . Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

15 . Regulatory information

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted.

Label requirements

Risk phrases	This product is not classified according to EU legislation.
Additional warning phrases	Safety data sheet available for professional user on request.
Other regulations	
Europe inventory	All components are listed or exempted.
United States inventory (TSCA 8b)	All components are listed or exempted.
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	Not determined.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	Not determined.

16 . Other information

Full text of R-phrases referred to in sections 2 and 3
R65- Harmful: may cause lung damage if swallowed.
R66- Repeated exposure may cause skin dryness or cracking.

History

Date of issue/ Date of revision 25/03/2009.

Date of previous issue 23/03/2009.

Prepared by Product Stewardship Group

Notice to reader

✔ Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name	Castrol Power 1 TTS 2T	Product code	465276-IT01	Page:	4/5
Version	4	Date of issue	25 March 2009	Format	United Kingdom (UK)
				Language	ENGLISH (ENGLISH)

Product name

Castrol Power 1 TTS 2T

Product code 465276-IT01

Page: 5/5

Version 4

Date of issue 25 March 2009

Format United Kingdom
(UK)

Language ENGLISH

(United Kingdom)

(ENGLISH)