Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04 Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking **Product identifier** 1.1 febi 24196 antifreeze Article number 24196 1.2 Relevant identified uses of the substance or mixture and uses advised against 1.2.1 Relevant uses Anti-freezing agents 1.2.2 Uses advised against For all uses not specified in SECTION 1.2.1 1.3 Details of the supplier of the safety data sheet Company Ferdinand Bilstein GmbH + Co. KG Wilhelmstr. 47 58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com Address enquiries to **Technical information** info@febi.com Safety Data Sheet info@febi.com 1.4 Emergency telephone number Advisory body +49 (0)89-19240 (24h) (english) +49 2333 911-0 Company **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. 2.2 Label elements The product is classified and required to be labelled in accordance with EC-Directives Hazard pictograms Signal word WARNING Contains: Ethylene glycol Hazard statements H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand. **Precautionary statements** P102 Keep out of reach of children. P260 Do not breathe vapours. P270 Do no eat, drink or smoke when using this product.

2.3 Other hazards

Physico-chemical hazards	No particular hazards known.
Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Other hazards	none

disposal.

P314 Get medical advice / attention if you feel unwell.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 2 / 9

# **SECTION 3: Composition / Information on ingredients**

#### Product-type:

#### The product is a mixture.

	Range [%]	Substance	
	30 - < 35 Ethylene glycol		
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX		
			Tox. 4: H302 - STOT RE 2: H373
SEC	Comment on com		Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%. For full text of H-statements and R-phrases: see SECTION 16.
SEC	FIION 4. FIISt alu	measures	
4.1	Description of fi	rst aid measure	5
	General information	on	Change soaked clothing.
	Inhalation		Ensure supply of fresh air. In the event of symptoms seek for medical treatment.
	Skin contact		In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
	Eye contact		Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Ingestion		Seek medical advice immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.
4.2	Most important symptoms and effects, both acute and delayed No information available.		
4.3	3 Indication of any immediate medical attention and special treatment needed		lical attention and special treatment needed
			Treat symptomatically. Forward this sheet to the doctor.
SEC	TION 5: Fire-fight	ing measures	
5.1	Extinguishing m	nedia	
	Suitable extinguis	hing media	Carbon dioxide. Water spray jet. Dry powder. Foam.
	Extinguishing mee be used	dia that must not	Full water jet.
5.2	Special hazards	arising from the	e substance or mixture
			Risk of formation of toxic pyrolysis products. Carbon monoxide (CO)
5.3	Advice for firefig	ghters	
			Use self-contained breathing apparatus.
			Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
SEC	TION 6: Accident	al release meas	Jres

#### 6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 3 / 9

6.2	Environmental precautions	
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.
6.3	Methods and material for contain	nment and cleaning up
		Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous earth). Dispose of absorbed material in accordance within the regulations.
6.4	Reference to other sections	
		See SECTION 8+13
SEC	CTION 7: Handling and storage	
7.1	Precautions for safe handling	
		Use only in well-ventilated areas.
		Do not eat, drink or smoke when using this product.
		Use barrier skin cream.
		Wash hands before breaks and after work.
		Cloths contaminated with product should not be kept in trouser pockets.
		Take off contaminated clothing and wash before reuse.
		Contaminated work clothing should not be allowed out of the workplace.
7.2	Conditions for safe storage, incl	uding any incompatibilities
		Keep only in original container. Prevent penetration into the ground.
		Do not store together with oxidizing agents. Do not store together with food and animal food/diet.
		Keep container tightly closed. Keep container in a well-ventilated place. Protect from heat/overheating.
7.3	Specific end use(s)	
-		See product upp SECTION 4.2

See product use, SECTION 1.2

# Safety Data Sheet 1907/2006/EC - REACH (GB) febi 24196 antifreeze Article number 24196

# Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 4 / 9

#### **SECTION 8: Exposure controls / personal protection**

#### 8.1 Control parameters

#### Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
30 - < 35	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	Long-term exposure: 20 ppm, 52 mg/m³, Vapour, particulate: 10 mg/m³
	Short-term exposure (15-minute): 40 ppm, 104 mg/m <sup>3</sup>

# Ingredients with occupational

# exposure limits to be monitored (EU) Range [%] Substance / EC LIMIT VALUES 30 - < 35 Ethylene glycol CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX Eight hours: 20 ppm, 52 mg/m<sup>3</sup>, H Short-term (15-minute): 40 ppm, 104 mg/m<sup>3</sup>

#### DNEL

Range [%]	Substance
30 - < 35	Ethylene glycol, CAS: 107-21-1
	Industrial, dermal, Long-term - systemic effects: 106 mg/m <sup>3</sup> .
	Industrial, inhalative, Long-term - local effects: 35 mg/m <sup>3</sup> .
	general population, dermal, Long-term - systemic effects: 53 mg/m <sup>3</sup> .
	general population, inhalative, Long-term - local effects: 7 mg/m <sup>3</sup> .
PNEC	
Range [%]	Substance

Range [%]	Substance
30 - < 35	Ethylene glycol, CAS: 107-21-1
	soil, 1,53 mg/kg.
	sediment (freshwater), 20,9 mg/kg.
	sewage treatment plants (STP), 199,5 mg/l.
	seawater, 1 mg/l.
	freshwater, 10 mg/l.

#### 8.2 Exposure controls

Ensure adequate ventilation on workstation.
If there is a risk of splashing: Safety glasses.
The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >480 min (EN 374).
Light protective clothing.
Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin. Do not inhale vapours.
Breathing apparatus in the event of high concentrations. Short term: filter apparatus, combination filter A-P2.
not determined
Comply with applicable environmental regulations limiting discharge to air, water and soil.

# Safety Data Sheet 1907/2006/EC - REACH (GB) febi 24196 antifreeze Article number 24196

# Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 5 / 9

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Form	liquid
Color	blue
Odor	mild
Odour threshold	not applicable
pH-value	7,5 - 9
pH-value [1%]	not determined
Boiling point [°C]	not determined
Flash point [°C]	> 100 (DIN 51758)
Flammability (solid, gas) [°C]	> 400 (DIN 51794)
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	no
Vapour pressure/gas pressure [kPa]	< 0,01 (20°C)
Density [g/ml]	~ 1,07 (DIN 51757)
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	not applicable
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not determined

#### 9.2 Other information

none

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reactions known if used as directed.

#### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents.

#### 10.4 Conditions to avoid

See SECTION 7.2.

#### 10.5 Incompatible materials

No information available.

#### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 6 / 9

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product
ATE-mix, oral, 1606,5 mg/kg bw.

Range [%]	Substance
30 - < 35	Ethylene glycol, CAS: 107-21-1
	LD50, dermal, mouse: > 3500 mg/kg.
	LD50, oral, Rat: 7712 mg/kg.
	LC50, inhalative, Rat: > 2,5 mg/l 6h.
	LDLo, oral, Human: ca. 1600 mg/kg.

Serious eye damage/irritation	not determined
Skin corrosion/irritation	not determined
Respiratory or skin sensitisation	not determined
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	not determined
Reproduction toxicity	not determined
Carcinogenicity	not determined
General remarks	
	The toxicity data

listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Range [%]	Substance
30 - < 35	Ethylene glycol, CAS: 107-21-1
	LC50, (96h), Pimephales promelas: 72860 mg/l.
	EC50, (96h), Selenastrum capricornutum: 6500 - 13000 mg/l.
	EC50, (48h), Daphnia magna: > 100 mg/l OECD 202.

#### 12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 7 / 9

#### 12.6 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment or into the drainage. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

#### Product

	Dispose of as hazardous waste. Disposal in an incineration plant in accordance with the regulations of the local authorities.
Waste no. (recommended)	160114*
Contaminated packaging	
	Uncontaminated packaging may be taken for recycling.
	Packaging that cannot be cleaned should be disposed of as for product.
Waste no. (recommended)	150110* 150102

#### **SECTION 14: Transport information**

#### 14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

#### 14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS" IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

#### 14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

#### 14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

#### 14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

#### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 8 / 9

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

15.1	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture		
	EEC-REGULATIONS	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC	
	TRANSPORT-REGULATIONS	DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).	
	NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4	
	- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.	
	- VOC (1999/13/CE)	not applicable	
15.2	Chemical safety assessment		
		not applicable	
SEC	TION 16: Other information		
16.1	Hazard statements (SECTION 3)		
		H373 May cause damage to organs through prolonged or repeated exposure. H302 Harmful if swallowed.	
16.2	Abbreviations and acronyms:		
		ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging DMEL = Derived Minimum Effect Level DNEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration ECB = European Chemicals Bureau EEC = European Chemicals Bureau EEC = European Inventory of Existing Commercial Chemical Substances ELINCS = European List of Notified Chemical Substances GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IC50 = Inherinational Maritime Code for Dangerous Goods IUCLID = International Maritime Code for Dangerous Goods IUCLD = International Maritime Code for Dangerous Goods IUCLD = International Convention for the Prevention of Marine Pollution from Ships PBT = Presistent, Bioaccumulative and Toxic substance PNEC = Predicted No-Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals TLV®/TWA = Threshold limit value – time-weighted average TLV®/TWA = Threshold limit value – short-time exposure limit VOC = Volatile Organic Compounds VPUB = very Persistent and very Bioaccumulative	
16.3	Other information		
	Classification procedure	Acute Tox. 4: H302 Harmful if swallowed. (Calculation method)	

Acute Tox. 4: H302 Harmful if swallowed. (Calculation method) STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. (Calculation method)

# Safety Data Sheet 1907/2006/EC - REACH (GB) febi 24196 antifreeze Article number 24196

# Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 9 / 9

Modified position

SECTION 2 been added: H373 May cause damage to organs through prolonged or repeated exposure. SECTION 2 been added: STOT RE 2

SECTION 2 been added: H302 Harmful if swallowed.

SECTION 2 been added: Acute Tox. 4

SECTION 7 been added: Do not eat, drink or smoke when using this product.