



Granville ZeroCol 48 Green Antifreeze

1 Litre, 5 Litre, 20 Litre & 200 Litre

Product Description

Granville Sub-Zero Green is ethylene glycol based formulated for optimum performance in heavy duty diesel engine applications but equally suitable for light duty use. It employs established inhibitor technology and is phosphate and amine free. BTC classification type 3EN.

The inhibitors include organic acids in combination with borate, silicate and nitrite which are well known for their ability to provide excellent protection in heavy duty applications, particularly when there is potential for cavitation erosion-corrosion to occur.

The product uses sophisticated silicate stabilisation technology to eliminate the potential for formation of silicate gel often observed with inferior products whilst other additives ensure good compatibility with hard water and prevent the formation of scale that can result from the use of hard water.

Product Benefits

- * Phosphate and Amine free
- * Superior cold weather protection
- * 3 year life
- * Excellent anti corrosion inhibitors

Directions for Use

As recommended by the engine manufacturer.

Dosage Information

Freeze Protection:

- * -12°C @ 25% concentration by volume
- * -22°C @ 33% concentration by volume
- * -40°C @ 50% concentration by volume

Storage Instructions

Store sealed in a cool, dry place.

Shelf Life

3 Years from date of manufacture.



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	2597	5020618025979
5 Litre	2602	5020618026020
20 Litre	2600	5020618026006
200 Litre	2599	5020618025993





Granville Zerocol 48 Green Antifreeze

1 Litre, 5 Litre, 20 Litre & 200 Litre

Specification Information

Exceeds the requirements of: ASTM D3306, ASTM D 4985, ASTM D 6210, SAE J 1034, BS 6580 (2010), AFNOR NF R15-601, JIS K2234.

Meets the requirements of: MAN 324, Cummins ES 14603, Leyland, Fiat/Iveco, MTU, Perkins, John Deere

Appearance	:	Clear Blue/Green liquid
Odour	:	Odourless
Specific Gravity	:	1.128 (Typical)
Solubility	:	Miscible in water
Flashpoint	:	111°C

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

