Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04 Page 1 / 9

SEC	TION 1: Identification of the subst	ance/mixture and of the company/undertaking
1.1	Product identifier	
		febi 26580 antifreeze Article number 26582, 26581, 26580
1.2	Relevant identified uses of the su	ubstance or mixture and uses advised against
1.2.1	Relevant uses	
		Anti-freezing agents
1.2.2	Uses advised against	
		For all uses not specified in SECTION 1.2.1
1.3	1.3 Details of the supplier of the safety data sheet	
	Company	Ferdinand Bilstein GmbH + Co. KG Wilhelmstr. 47 58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com
	Address enquiries to	
	Technical information	info@febi.com
	Safety Data Sheet	info@febi.com
1.4	Emergency telephone number	
	Advisory body	+49 (0)89-19240 (24h) (english)
	Company	+49 2333 911-0
SEC	TION 2: Hazards identification	
2.1	Classification of the substance o	r mixture
		Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure.
2.2	Label elements	
		The product is classified and required to be labelled in accordance with EC-Directives
	Hazard pictograms	

Signal word	WARNING
Contains:	Ethylene glycol
Hazard statements	H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	 P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. P270 Do no eat, drink or smoke when using this product. P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell. P314 Get medical advice / attention if you feel unwell. P501 Dispose of contents / container to an appropriate treatment and disposal facility in

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04 P

Page 2 / 9

2.3 Other hazards

Physico-chemical hazards	No particular hazards known.
Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	none

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
40 - 60	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373

Comment on component parts	Comme	ent on	compone	ent parts
----------------------------	-------	--------	---------	-----------

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%. For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

~

4.1	Description of first aid measures General information	Change soaked clothing.
	Inhalation	Ensure supply of fresh air. In the event of symptoms seek for medical treatment.
	Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
	Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Tiredness Spasms Diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide. Water spray jet. Dry powder. Foam.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products. Carbon monoxide (CO)

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04 Page 3 / 9

5.3 Advice for firefighters Use self-contained breathing apparatus. Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations. SECTION 6: Accidental release measures Personal precautions, protective equipment and emergency procedures 6.1 High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water. 6.2 Environmental precautions Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater. 6.3 Methods and material for containment and cleaning up Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous earth). Dispose of absorbed material in accordance within the regulations. Reference to other sections 6.4 See SECTION 8+13 **SECTION 7: Handling and storage** 7.1 Precautions for safe handling Use only in well-ventilated areas. Remove soiled or soaked clothing immediately. Do not eat, drink or smoke when using this product. Use barrier skin cream. Wash hands before breaks and after work. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse. 7.2 Conditions for safe storage, including any incompatibilities Keep only in original container. Prevent penetration into the ground. Do not store together with oxidizing agents. Do not store together with food and animal food/diet. Keep container tightly closed. Keep container in a well-ventilated place. 7.3 Specific end use(s)

See product use, SECTION 1.2

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04 Page 4 / 9

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
40 - 60	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	Long-term exposure: 20 ppm, 52 mg/m ³ , Vapour, particulate: 10 mg/m ³
	Short-term exposure (15-minute): 40 ppm, 104 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

exposure mints to	be monitored (EO)	
Range [%]	Range [%] Substance / EC LIMIT VALUES	
40 - 60	Ethylene glycol	
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX	
Eight hours: 20 ppm, 52 mg/m ³ , H		
	Short-term (15-minute): 40 ppm, 104 mg/m ³	

DNEL

Range [%]	Substance	
40 - 60	Ethylene glycol, CAS: 107-21-1	
	Industrial, dermal, Long-term - systemic effects: 106 mg/m ³ .	
	Industrial, inhalative, Long-term - local effects: 35 mg/m ³ .	
	general population, dermal, Long-term - systemic effects: 53 mg/m ³ .	
	general population, inhalative, Long-term - local effects: 7 mg/m ³ .	
PNEC		
Range [%]	Substance	
40 - 60	Ethylene glycol, CAS: 107-21-1	

Range [%]	Substance	
40 - 60	Ethylene glycol, CAS: 107-21-1	
	soil, 1,53 mg/kg.	
	sediment (freshwater), 20,9 mg/kg.	
	sewage treatment plants (STP), 199,5 mg/l.	
	seawater, 1 mg/l.	
	freshwater, 10 mg/l.	

8.2 Exposure controls

•	
Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	If there is a risk of splashing: Safety glasses.
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >480 min (EN 374).
Skin protection	Light protective clothing.
Other	Avoid contact with eyes and skin. Do not inhale vapours. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.
Respiratory protection	Breathing apparatus in the event of high concentrations. Short term: filter apparatus, combination filter A-P2.
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	See SECTION 6+7.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04

Page 5 / 9

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	green
Odor	mild
Odour threshold	not determined
pH-value	7,5 - 9
pH-value [1%]	not determined
Boiling point [°C]	not determined
Flash point [°C]	> 100 (DIN 51758)
Flammability (solid, gas) [°C]	> 400 (DIN 51794)
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	no
Vapour pressure/gas pressure [kPa]	< 0,01 (20°C)
Density [g/ml]	~ 1,06 (DIN 51757) (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	not determined
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not determined

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04

Page 6 / 9

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, oral, 1063 mg/kg bw.

Range [%]	Substance
40 - 60 Ethylene glycol, CAS: 107-21-1	
	LD50, dermal, mouse: > 3500 mg/kg.
LD50, oral, Rat: 7712 mg/kg.	
LC50, inhalative, Rat: > 2,5 mg/l 6h.	
LDLo, oral, Human: ca. 1600 mg/kg.	

Serious eye damage/irritation	not determined
Skin corrosion/irritation	not determined
Respiratory or skin sensitisation	not determined
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	not determined
Reproduction toxicity	not determined
Carcinogenicity	not determined
General remarks	Frequent persistent contact with the skin can cause skin irritation.
	The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	Range [%] Substance	
40 - 60 Ethylene glycol, CAS: 107-21-1		
	LC50, (96h), Pimephales promelas: 72860 mg/l.	
EC50, (96h), Selenastrum capricornutum: 6500 - 13000 mg/l.		
	EC50, (48h), Daphnia magna: > 100 mg/l OECD 202.	

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	Inherently biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04

Page 7 / 9

12.6 Other adverse effects

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

	Dispose of as hazardous waste. Disposal in an incineration plant in accordance with the regulations of the local authorities.
Waste no. (recommended)	160114*
Contaminated packaging	
	Uncontaminated packaging may be taken for recycling. Packaging that cannot be cleaned should be disposed of as for product.
Waste no. (recommended)	150110*

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS
Inland navigation (ADN)	NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS" IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04

Page 8 / 9

SECTION	15: Regulatory information	
	ty, health and environmental REGULATIONS	regulations/legislation specific for the substance or mixture 1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2009: 75/224/EEC (2008/47/EC): 452/2010/EC
TDAN	NSPORT-REGULATIONS	1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).
	ONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
NAU	ONAL RECOLATIONO (OD).	CHIP 3/ CHIP 4
for p	serve employment restrictions eople	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VO	C (1999/13/CE)	0%
15.2 Chei	mical safety assessment	
		not applicable
SECTION	16: Other information	
16.1 Haza	ard statements (SECTION 3)	
	. ,	H373 May cause damage to organs through prolonged or repeated exposure. H302 Harmful if swallowed.
16.2 Abb	reviations and acronyms:	
	-	ADR = Accord européen relatif au transport international des marchandises Dangereuses par
		Route RID = Règlement concernant le transport international ferroviaire de marchandises
		dangereuses ADN = Accord européen relatif au transport international des marchandises dangereuses par
		voie de navigation intérieure
		CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging
		DMEL = Derived Minimum Effect Level
		DNEL = Derived No Effect Level EC50 = Median effective concentration
		ECB = European Chemicals Bureau
		EEC = European Economic Community EINECS = European Inventory of Existing Commercial Chemical Substances
		ELINCS = European List of Notified Chemical Substances
		GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association
		IBC-Code = International Code for the Construction and Equipment of Ships carrying
		Dangerous Chemicals in Bulk
		IC50 = Inhibition concentration, 50% IMDG = International Maritime Code for Dangerous Goods
		IUCLID = International Uniform ChemicaL Information Database
		LC50 = Lethal concentration, 50% LD50 = Median lethal dose
		MARPOL = International Convention for the Prevention of Marine Pollution from Ships PBT = Persistent, Bioaccumulative and Toxic substance PNEC = Predicted No-Effect Concentration
		REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
		TLV®/TWA = Threshold limit value – time-weighted average
		TLV®STEL = Threshold limit value – short-time exposure limit VOC = Volatile Organic Compounds
		vPvB = very Persistent and very Bioaccumulative
16.3 Othe	er information	
Class	sification procedure	Acute Tox. 4: H302 Harmful if swallowed. (Calculation method) STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. (Calculation method)
Modi	fied position	SECTION 2 been added: H373 May cause damage to organs through prolonged or repeated exposure.
		SECTION 2 been added: STOT RE 2
		SECTION 7 been added: Do not eat, drink or smoke when using this product.
		SECTION 15 been added: 2 (self-classification)
		SECTION 15 been added: Storage class 12 (VCI)

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04 Page 9 / 9