Safety Data Sheet 1907/2006/EC - REACH (GB) febi 32590 Gear oil 75W - 90 Article number 32590

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

febi 32590 Gear oil 75W - 90 Article number 32590

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

> Wilhelmstr. 47 58256 Ennepetal / GERMANY

Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com **Safety Data Sheet** info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

Company +49 2333 911-0

SECTION 2: Hazards identification

Classification of the substance or mixture

Eye Irrit. 2: H319 Causes serious eye irritation.

2.2 Label elements

The product is classified and required to be labelled in accordance with EC-Directives

Hazard pictograms

Signal word WARNING

H319 Causes serious eye irritation. **Hazard statements**

Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice / attention.

Special labelling Contains: Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2-

yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl

(branched). EUH208 May produce an allergic reaction.

2.3 Other hazards

> Physico-chemical hazards No particular hazards known.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards No particular hazards known.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 2 / 9

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
25 - < 50	1-Decene, homopolymer, hydrogenated
	CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EINECS/ELINCS: 931-384-6, Reg-No.: 01-2119493620-38-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - Acute Tox. 4: H302 - Skin Sens. 1: H317 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411
0,1 - < 1	Triarylthiophosphat
	CAS: 597-82-0, EINECS/ELINCS: 209-909-9
	GHS/CLP: Repr. 2: H361fd - Aquatic Chronic 3: H412
2,5 - < 5	Polysulfides, di-tert-Bu
	CAS: 68937-96-2, EINECS/ELINCS: 273-103-3
	GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 4: H413

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%.

For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek for medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.

Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).

Safety Data Sheet 1907/2006/EC - REACH (GB) febi 32590 Gear oil 75W - 90 Article number 32590

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 3 / 9

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas.

Use solvent-resistant equipment.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Cloths contaminated with product should not be kept in trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 4 / 9

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
25 - < 50	1-Decene, homopolymer, hydrogenated
	CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX
	Long-term exposure: 5 mg/m³, OSHA PEL

DNEL

Range [%]	Substance
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	Industrial, inhalative, Long-term - systemic effects: 8,56 mg/m³/8h (ECHA CHEM).
	Industrial, dermal, Long-term - systemic effects: 12,5 mg/kg/8h (ECHA CHEM).

PNEC

Range [%]	Substance
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	sewage treatment plants (STP), 24.33 mg/l (ECHA CHEM).
	soil, 2,54 mg/kg soil dw (ECHA CHEM).
	sediment (seaater), 0,313 mg/kg (ECHA CHEM).
	sediment (freshwater), 3,13 mg/kg (ECHA CHEM).
	seawater, 0,00012 mg/l (ECHA CHEM).
	freshwater, 0,0012 mg/l (ECHA CHEM).

8.2 Exposure controls

Eye protection Safety glasses.

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm/ Nitrile rubber, >120 min (EN 374).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective

supplier

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Respiratory protection not applicable

Thermal hazards No information available.

Delimitation and monitoring of the environmental exposition

No information available.

See SECTION 6+7.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 5 / 9

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Color brown

Odor characteristic

Odour threshold not determined

pH-value not applicable

pH-value [1%] not applicable

Boiling point [°C] not applicable

Flash point [°C] 210 (EN ISO 2592 (COC))

Flammability (solid, gas) [°C] not determined

Lower explosion limit not applicable

Upper explosion limit not applicable

Oxidizing properties no

Vapour pressure/gas pressure [kPa] not determined

Density [g/ml] 0,866 (DIN 51757) (15 °C / 59,0 °F)

 Bulk density [kg/m³]
 not applicable

 Solubility in water
 immiscible

 Partition coefficient [n-octanol/water]
 not determined

Viscosity 114 mm²/s 40°C (DIN 51562)

Relative vapour density determined

in air

not determined

Evaporation speed not determined

Melting point [°C] not determined

Autoignition temperature [°C] not applicable

Decomposition temperature [°C] not determined

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 6 / 9

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product	
ATE-mix, oral, > 5000 mg/kg bw.	

Range [%]	Substance
25 - < 50	1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
	LD50, dermal, Rabbit: > 2000 mg/kg (Lit.).
	LD50, oral, Rat: > 2000 mg/kg (Lit.).
	LC50, inhalative, Rat: > 5000 mg/m³ (Lit.).
1 - < 2,5	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	LD50, oral, Rat: 2000 mg/kg bw OECD 401 (ECHA CHEM).

Serious eye damage/irritation not determined
Skin corrosion/irritation not determined
Respiratory or skin sensitisation Non-sensitizing.
Specific target organ toxicity — not determined single exposure
Specific target organ toxicity — not determined repeated exposure

Mutagenicity not determined
Reproduction toxicity not determined
Carcinogenicity not determined

General remarks

Toxicological data of complete product are not available. The toxiclogical data are those of the pure product.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	Substance
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EL50, (48h), Daphnia magna: ~ 91,4 mg/l OECD 202 (ECHA CHEM).
	EL50, (96h), Selenastrum capricornutum: > 15 mg/l OECD 201 (ECHA CHEM).
	LL50, (96h), Oncorhynchus mykiss: ~ 24 mg/l OECD 203 (ECHA CHEM).

12.2 Persistence and degradability

Behaviour in environment not determined compartments

Behaviour in sewage plant not determined Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

Safety Data Sheet 1907/2006/EC - REACH (GB) febi 32590 Gear oil 75W - 90 Article number 32590

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 7 / 9

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

No classification on the basis of the calculation procedure of the preparation directive.

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

150110* Waste no. (recommended)

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

NO DANGEROUS GOODS Inland navigation (ADN)

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

Safety Data Sheet 1907/2006/EC - REACH (GB) febi 32590 Gear oil 75W - 90 Article number 32590

Ferdinand Bilstein GmbH + Co. KG
Date printed 05.06.2015, Revision 05.06.2015



Version 05. Supersedes version: 04

Page 8 / 9

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach);

1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC

TRANSPORT-REGULATIONS DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

CHIP 3/ CHIP 4

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (1999/13/CE) not applicable

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H412 Harmful to aquatic life with long lasting effects.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H226 Flammable liquid and vapour.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

Route

RID = Règlement concernant le transport international ferroviaire de marchandises

dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par

voie de navigation intérieure

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

Safety Data Sheet 1907/2006/EC - REACH (GB) febi 32590 Gear oil 75W - 90 Article number 32590

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 9 / 9

16.3 Other information

Classification procedure Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)

Modified position SECTION 2 deleted: WARNING

SECTION 2 deleted: Skin Sens. 1 SECTION 2 been added: Skin Irrit. 2

SECTION 2 been added: H315 Causes skin irritation.

SECTION 2 deleted: H317 May cause an allergic skin reaction.

SECTION 2 deleted: Ausrufezeichen

SECTION 2 deleted: H315 Causes skin irritation.

SECTION 2 deleted: Skin Irrit. 2
SECTION 2 been added: Eye Irrit. 2
SECTION 2 been added: Ausrufezeichen
SECTION 2 been added: WARNING

SECTION 2 been added: H319 Causes serious eye irritation.

SECTION 15 been added: 2 (self-classification)

SECTION 15 deleted: 1, gem. VwVwS vom 27.07.2005

SECTION 16 been added: Calculation method SECTION 16 deleted: Calculation method