ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

febi 32600 automatic transmission fluid (ATF) Article number 32600, 32605

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47 58256 Ennepetal / GERMANY

Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

Company +49 2333 911-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

No classification.

2.2 Label elements

The product is required to be labelled in accordance with GHS/CLP-Directives.

Hazard pictogramsnoneSignal wordnoneHazard statementsnonePrecautionary statementsnone

Special labelling EUH210 Safety data sheet available on request.

2.3 Other hazards

Physico-chemical hazards No particular hazards known.

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards No particular hazards known.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 2 / 8

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

| Range [%] | Substance |
|-----------|---|
| 25 - 50 | Distillates (petroleum), hydrotreated light paraffinic |
| | CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-xxxx |
| | GHS/CLP: Asp. Tox. 1: H304 |
| 1 - < 2,5 | Alkoxy sulfolane |
| | GHS/CLP: Aquatic Chronic 2: H411 |
| 1 - < 2,5 | Methacrylate copolymer |
| | EINECS/ELINCS: Polymer |
| | GHS/CLP: Eye Irrit. 2: H319 |

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%.

For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek for medical treatment.

Skin contact When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contactRinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.

Seek medical advice immediately.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 3 / 8

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water. Use personal protective equipment.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas.

Use solvent-resistant equipment.

The product is combustible.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Cloths contaminated with product should not be kept in trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

| Range [%] | Substance |
|-----------|---|
| 25 - 50 | Distillates (petroleum), hydrotreated light paraffinic |
| | CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-xxxx |
| | Long-term exposure: 5 mg/m³, ACGIH TLV (OIL MIST) |

ebi bilstein

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 4 / 8

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Eye protection Safety glasses.

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information

> 0,4 mm: Nitrile rubber, >480 min (EN 374). > 0,4 mm: Neoprene, >480 min (EN 374).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective

supplier.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Respiratory protection not applicable

Thermal hazards No information available.

Delimitation and monitoring of the See SECTION 6+7.

environmental exposition

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid
Color red

Odor characteristic **Odour threshold** not determined pH-value not applicable pH-value [1%] not applicable Boiling point [°C] not applicable 205 (EN ISO 2592) Flash point [°C] Flammability (solid, gas) [°C] not determined Lower explosion limit not applicable Upper explosion limit not applicable

Oxidizing properties no

Vapour pressure/gas pressure [kPa] not determined

Density [g/ml] 0,85 (DIN 51757) (15 °C / 59,0 °F)

 Bulk density [kg/m³]
 not applicable

 Solubility in water
 immiscible

 Partition coefficient [n-octanol/water]
 not determined

Viscosity 30,6 mm²/s 40°C (DIN 51562)

Relative vapour density determined

in air

not determined

Evaporation speed not determined

Melting point [°C] not determined

Autoignition temperature [°C] not applicable

Decomposition temperature [°C] not determined

9.2 Other information

No information available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 5 / 8

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Range [% | Substance |
|----------|--|
| 1 - < 2, | 5 Alkoxy sulfolane |
| | LD50, dermal, Rabbit: > 2000 mg/kg (Lit.). |
| | LD50, oral, Rat: > 5000 mg/kg (Lit.). |

Serious eye damage/irritation not determined Skin corrosion/irritation not determined Respiratory or skin sensitisation not determined Specific target organ toxicity not determined single exposure Specific target organ toxicity not determined repeated exposure Mutagenicity not determined Reproduction toxicity not determined Carcinogenicity not determined **General remarks**

No classification on the basis of the calculation procedure of the preparation directive.

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

| Range [%] | Substance |
|-----------|--|
| 1 - < 2,5 | Alkoxy sulfolane |
| | LC50, (96h), fish: 4,2 mg/l (Lit.). |
| | EC50, (72h), Algae: 3,5 mg/l (Lit.). |
| | EC50, (48h), Daphnia magna: 2,5 mg/l (Lit.). |

12.2 Persistence and degradability

Behaviour in environment not determined

compartments

Behaviour in sewage plant not determined **Biological degradability** not determined



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 6 / 8

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

No classification on the basis of the calculation procedure of the preparation directive.

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

1501103 150102 150104

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to

NO DANGEROUS GOODS

ADR/RID

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 7 / 8

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach);

1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC

TRANSPORT-REGULATIONS DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

CHIP 3/ CHIP 4

- Observe employment restrictions

for people

- VOC (1999/13/CE) not applicable

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H411 Toxic to aquatic life with long lasting effects.

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.06.2015, Revision 05.06.2015

Version 05. Supersedes version: 04

Page 8 / 8

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform Chemical Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position SECTION 3 been added: Methacrylate copolymer

SECTION 3 been added: 3-(decyloxy)tetrahydrothiophene 1,1-dioxide

SECTION 3 been added: Distillates (petroleum), hydrotreated light paraffinic

SECTION 15 been added: EUH210 Safety data sheet available on request.

SECTION 7 been added: The product is combustible.