Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015

Version 05. Supersedes version: 04

Page 1 / 9

SEC	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1	Product identifier		
		febi 01381 antifreeze Article number 80325, 22274, 22272, 12710, 01381, 33830	
1.2	Relevant identified uses of the se	ubstance or mixture and uses advised against	
1.2.1	I Relevant uses		
		Anti-freezing agents	
1.2.2	2 Uses advised against		
		For all uses not specified in SECTION 1.2.1	
1.3	Details of the supplier of the set	studete cheet	
1.5	Details of the supplier of the safe Company	Ferdinand Bilstein GmbH + Co. KG	
	Company	Wilhelmstr. 47	
		58256 Ennepetal / GERMANY	
		Phone +49 2333 911-0 Fax +49 2333 911-444	
		Homepage www.febi.com	
		E-mail info@febi.com	
	Address enquiries to		
	Technical information	info@febi.com	
	Safety Data Sheet	info@febi.com	
1.4	Emergency telephone number		
	Advisory body	+49 (0)89-19240 (24h) (english)	
	Company	+49 2333 911-0	
SEC	TION 2: Hazards identification		
SEU	SECTION 2: Hazards identification		
3EC 2.1	Classification of the substance of		
		or mixture Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure.	
		Acute Tox. 4: H302 Harmful if swallowed.	
2.1	Classification of the substance of	Acute Tox. 4: H302 Harmful if swallowed.	
2.1	Classification of the substance of	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure.	
2.1	Classification of the substance of Label elements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements Hazard pictograms	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed.	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains:	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand.	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. P270 Do no eat, drink or smoke when using this product.	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. P270 Do no eat, drink or smoke when using this product. P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell.	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives	
2.1 2.2	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements Precautionary statements Other hazards	 Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives Image: Content of the product of the product	
2.1 2.2	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements Precautionary statements Other hazards Physico-chemical hazards	Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives WARNING Ethylene glycol H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure. P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. P270 Do no eat, drink or smoke when using this product. P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell. P314 Get medical advice / attention if you feel unwell. P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
2.1 2.2	Classification of the substance of Label elements Hazard pictograms Signal word Contains: Hazard statements Precautionary statements Other hazards	 Acute Tox. 4: H302 Harmful if swallowed. STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. The product is classified and required to be labelled in accordance with EC-Directives Image: Content of the product of the product	

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 2 / 9

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

	Γ	
	Range [%] Substance	
	90 - < 95 Ethylene glyco	
		I, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	GHS/CLP: Act	ute Tox. 4: H302 - STOT RE 2: H373
	Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%. For full text of H-statements and R-phrases: see SECTION 16.
SEC	CTION 4: First aid measures	
4.1	Description of first aid measure	ures
	General information	Change soaked clothing.
	Inhalation	Ensure supply of fresh air. In the event of symptoms seek for medical treatment.
	Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
	Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.
4.2	Most important symptoms ar	nd effects, both acute and delayed
		No information available.
4.3	Indication of any immediate r	medical attention and special treatment needed
		Treat symptomatically. If swallowed or in the event of vomiting, risk of product entering the lungs. Forward this sheet to the doctor.
SEC	TION 5: Fire-fighting measure	S
5.1	Extinguishing media	
	Suitable extinguishing media	Carbon dioxide. Water spray jet. Dry powder. Foam.
	Extinguishing media that must n be used	ot Full water jet.
5.2	Special hazards arising from	the substance or mixture

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products. Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

Ferdinand Bilstein GmbH + Co. KG Date printed 03.06.2015, Revision 03.06.2015

Version 05. Supersedes version: 04

Page 3 / 9

SEC	SECTION 6: Accidental release measures		
6.1	Personal precautions, protective	equipment and emergency procedures	
		High risk of slipping due to leakage/spillage of product.	
		Forms slippery surfaces with water.	
6.2	Environmental precautions		
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.	
6.3	Methods and material for contain	ment and cleaning up	
		Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous	
		earth). Dispose of absorbed material in accordance within the regulations.	
6.4	Reference to other sections		
0.4		See SECTION 8+13	
SEC	TION 7: Handling and storage		
3EC	non 7. Handling and storage		
7.1	Precautions for safe handling		
		Use only in well-ventilated areas.	
		Do not eat, drink or smoke when using this product.	
		Use barrier skin cream.	
		Wash hands before breaks and after work.	
		Cloths contaminated with product should not be kept in trouser pockets.	
		Contaminated work clothing should not be allowed out of the workplace.	
		Take off contaminated clothing and wash before reuse.	
7.2	Conditions for safe storage, inclu	iding any incompatibilities	
		Keep only in original container.	
		Prevent penetration into the ground.	
		Do not store together with oxidizing agents. Do not store together with food and animal food/diet.	
		Keep container tightly closed.	
		Keep container in a well-ventilated place. Protect from heat/overheating.	
		roteet nom neakovernealing.	
7.3	Specific end use(s)		
		See product use, SECTION 1.2	

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015

Version 05. Supersedes version: 04 Page 4 / 9

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
90 - < 95	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	Long-term exposure: 20 ppm, 52 mg/m ³ , Vapour, particulate: 10 mg/m ³
	Short-term exposure (15-minute): 40 ppm, 104 mg/m ³

Ingredients with occupational

exposure limits to be monitored (EU)

Range [%]	Substance / EC LIMIT VALUES
90 - < 95	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	Eight hours: 20 ppm, 52 mg/m ³ , H
	Short-term (15-minute): 40 ppm, 104 mg/m ³

DNEL

Range [%]	Substance
90 - < 95	Ethylene glycol, CAS: 107-21-1
	Industrial, dermal, Long-term - systemic effects: 106 mg/m ³ .
	Industrial, inhalative, Long-term - local effects: 35 mg/m ³ .
	general population, dermal, Long-term - systemic effects: 53 mg/m ³ .
	general population, inhalative, Long-term - local effects: 7 mg/m ³ .
PNEC	
Range [%]] Substance
90 - < 95	Ethylene glycol, CAS: 107-21-1

Range [%]	Substance
90 - < 95	Ethylene glycol, CAS: 107-21-1
	soil, 1,53 mg/kg.
[sediment (freshwater), 20,9 mg/kg.
	sewage treatment plants (STP), 199,5 mg/l.
	seawater, 1 mg/l.
	freshwater, 10 mg/l.

8.2 Exposure controls

•	
Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	Safety glasses.
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >480 min (EN 374).
Skin protection	Light protective clothing.
Other	Avoid contact with eyes and skin. Do not inhale vapours. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.
Respiratory protection	Breathing apparatus in the event of high concentrations. Short term: filter apparatus, combination filter A-P2.
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	See SECTION 6+7.

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04 Page 5 / 9

9.1 Information on basic physical and chemical properties

•	information on basic physical and	i chemical properties
	Form	liquid
	Color	red
	Odor	characteristic
	Odour threshold	not determined
	pH-value	7,5-9 (33%)
	pH-value [1%]	not determined
	Boiling point [°C]	120
	Flash point [°C]	> 110 (DIN 51758)
	Flammability (solid, gas) [°C]	> 400 (DIN 51794)
	Lower explosion limit	not determined
	Upper explosion limit	not determined
	Oxidizing properties	no
	Vapour pressure/gas pressure [kPa]	< 0,01 (20°C)
	Density [g/ml]	1,12 (DIN 51757)
	Bulk density [kg/m³]	not applicable
	Solubility in water	miscible
	Partition coefficient [n-octanol/water]	not determined
	Viscosity	15 mm²/s (20°C) (DIN 51562/T1)
	Relative vapour density determined in air	not determined
	Evaporation speed	not determined
	Melting point [°C]	not determined
	Autoignition temperature [°C]	not applicable
	Decomposition temperature [°C]	not determined

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2. Strong heating.

10.5 Incompatible materials

not determined

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015

Version 05. Supersedes version: 04 Page 6 / 9

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, oral, 529,6 mg/kg bw.

Range [%]	Substance
90 - < 95	Ethylene glycol, CAS: 107-21-1
	LD50, dermal, mouse: > 3500 mg/kg.
	LD50, oral, Rat: 7712 mg/kg.
	LC50, inhalative, Rat: > 2,5 mg/l 6h.
	LDLo, oral, Human: ca. 1600 mg/kg.

Serious eye damage/irritation	not determined
Skin corrosion/irritation	not determined
Respiratory or skin sensitisation	not determined
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	not determined
Reproduction toxicity	not determined
Carcinogenicity	not determined
General remarks	Frequent persistent contact with the skin can cause skin irritation.
	The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	9 [%] Substance	
90 - < 95	90 - < 95 Ethylene glycol, CAS: 107-21-1	
LC50, (96h), Pimephales promelas: 72860 mg/l. EC50, (96h), Selenastrum capricornutum: 6500 - 13000 mg/l.		

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04

Page 7 / 9

12.6 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment or into the drainage. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

	Dispose of as hazardous waste. Disposal in an incineration plant in accordance with the regulations of the local authorities.
Waste no. (recommended)	160114*
Contaminated packaging	
	Packaging that cannot be cleaned should be disposed of as for product. Uncontaminated packaging may be taken for recycling.
Waste no. (recommended)	150110* 150102

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS" IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04 P

Page 8 / 9

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1	5.1 Safety, health and environmental regulations/legislation specific for the substance or mixture		
	EEC-REGULATIONS	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC	
	TRANSPORT-REGULATIONS	DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).	
	NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4	
	- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.	
	- VOC (1999/13/CE)	0%	
15.2	Chemical safety assessment		
		not applicable	
SEC	TION 16: Other information		
16.1	Hazard statements (SECTION 3)		
		H373 May cause damage to organs through prolonged or repeated exposure. H302 Harmful if swallowed.	
16.2	Abbreviations and acronyms:		
		ADR = Accord européen relatif au transport international des marchandises Dangereuses Rib = Règlement concernant le transport international ferroviaire de marchandises dangereuses ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging DMEL = Derived Minimum Effect Level DNEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration ECB = European Chemicals Bureau EEC = European Chemicals Bureau EEC = European Economic Community EINECS = European List of Notified Chemical Substances GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IC50 = International Maritime Code for Dangerous Goods IUCLID = International Uniform ChemicaL Information Database LC50 = Lethal concentration, 50% LD50 = Median lethal dose MARPOL = International Convention for the Prevention of Marine Pollution from Ships PBT = Predicted No-Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals TLV®/TWA = Threshold limit value – time-weighted average TLV%STEL = Threshold limit value – short-time exposure limit VOC = Volatile Organic Compounds VPVB = very Persistent and very Bioaccumulative	
16.3	Other information		
10.3	Classification procedure	Acute Tox. 4: H302 Harmful if swallowed. (Calculation method)	

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. (Calculation method)

Ferdinand Bilstein GmbH + Co. KG

Date printed 03.06.2015, Revision 03.06.2015



Version 05. Supersedes version: 04 Page 9 / 9

Modified position

SECTION 2 been added: H373 May cause damage to organs through prolonged or repeated exposure. SECTION 2 been added: STOT RE 2 SECTION 2 been added: H302 Harmful if swallowed.

SECTION 2 been added: Acute Tox. 4