

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LUKOIL GENESIS SPECIAL FD 5W-20
Product code : 563115

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Engine oil
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : LUKOIL Lubricants Europe GmbH
Ölhafen Lobau – Uferstr. 8
1220 Wien
Austria

Telephone : +43 (1) 205 222 - 8800
Responsible/issuing person : info.product-safety@lukoil.com

1.4 Emergency telephone number

Telephone : +43 (1) 205 222 – 8800
(5d/08:00 – 17:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

Precautionary statements	: P102	Keep out of reach of children.
	Disposal:	
	P501	Dispose of contents/ container to an approved waste disposal plant.

Additional Labelling:

EUH210	Safety data sheet available on request.
EUH208	Contains: C14-16-18 Alkyl phenol. May produce an allergic reaction.

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Material can create slippery conditions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
 Hydrocarbons
 Additives

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. :			
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1 276-738-4 01-2119474889-13	Asp. Tox.1; H304	>= 70 - < 90
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1 276-738-4 01-2119474889-13		< 20
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28	Aquatic Chronic4; H413	>= 1 - < 2,5
C14-16-18 Alkyl phenol	01-2119498288-19	Skin Sens.1B; H317 Aquatic Chronic4; H413	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : First aider needs to protect himself.

If inhaled : If breathed in, move person into fresh air.
 Move to fresh air in case of accidental inhalation of vapours.

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

- In case of skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser.
If on clothes, remove clothes.
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.
Obtain medical attention.
When symptoms persist or in all cases of doubt seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort
Stomach/intestinal disorders
Vomiting
Pneumonia
irritant effects
- Risks : May cause eye irritation.
Risk of product entering the lungs on vomiting after ingestion.
Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry powder
Foam
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Extinguishing media - large fires Complete suit protecting

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

against chemicals

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Keep people away from and upwind of spill/leak.
Use personal protective equipment.
First aider needs to protect himself.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation, especially in confined areas.
The danger areas must be delimited and identified using relevant warning and safety signs.
Refer to section 15 for specific national regulation.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage.
Avoid subsoil penetration.
Do not contaminate water.
Prevent product from entering drains.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with oil absorbent material.
Offer surplus and non-recyclable solutions to a licensed disposal company.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Take care to avoid waste and spillage when weighing, loading and mixing the product.
Avoid formation of aerosol.
Use only in area provided with appropriate exhaust ventilation.
Provide exhaust ventilation close to floor level.
Do not get on skin or clothing.
Avoid inhalation, ingestion and contact with skin and eyes.

Advice on protection against : To avoid ignition of vapours by static electricity discharge, all

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

bis(nonylphenyl)amine : End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 0,62 mg/kg
End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 4,37 mg/m³
End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 0,31 mg/kg
End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 1,09 mg/m³
End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 0,31 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis(nonylphenyl)amine : Fresh water
Value: 0,1 mg/l
Marine water
Value: 0,01 mg/l
Fresh water sediment
Value: 132000 mg/kg
Marine sediment
Value: 13200 mg/kg
Soil
Value: 263000 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,40 mm
Directive : DIN EN 374
Viton (R)
480 min
0,70 mm
DIN EN 374

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

- butyl-rubber
120 min
0,70 mm
DIN EN 374
Neoprene
60 min
0,60 mm
DIN EN 374
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special work-place conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
- Skin and body protection : Flame retardant protective clothing
Workers should wear antistatic footwear.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
Respirator with filter type A
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Suitable respiratory equipment:
Self-contained breathing apparatus (EN 133)
- Protective measures : Wear suitable protective equipment.
Avoid contact with the skin and the eyes.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : light brown
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

pour point	:	<= -36 °C Method: ISO 3016
	:	No data available
Flash point	:	>= 200 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Burning rate	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Vapour density	:	No data available
Relative density	:	No data available
Density	:	0,848 g/cm ³ (20 °C) Method: DIN 51757
Bulk density	:	No data available
Water solubility	:	< 0,01 g/l (20 °C, 1.013 mbar)
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not determined
Auto-ignition temperature	:	No data available
Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity, dynamic	:	<= 6.600 mPa.s (-30 °C) Method: DIN 51377
Viscosity, kinematic	:	45 mm ² /s (40 °C)
Flow time	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Self-heating substances	:	No data available
Impact sensitivity	:	No data available
Surface tension	:	No data available
	:	No data available
Molecular weight	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is chemically stable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity	:	No data available
Acute inhalation toxicity	:	No data available
Acute dermal toxicity	:	No data available

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Acute toxicity (other routes of administration) : No data available

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 Rat: >= 5,53 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal Rabbit: > 2.000 mg/kg
Method: OECD Test Guideline 402

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 Rat: >= 5,53 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal Rabbit: > 2.000 mg/kg
Method: OECD Test Guideline 402

|| bis(nonylphenyl)amine:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg
Method: OECD Test Guideline 401
Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg
Method: OECD Test Guideline 402
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

slight irritation
Non persistent irritation

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 404

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Prolonged skin contact may cause skin irritation and/or dermatitis.
Based on available data, the classification criteria are not met.

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 404
Prolonged skin contact may cause skin irritation and/or dermatitis.
Based on available data, the classification criteria are not met.

|| bis(nonylphenyl)amine:

Species: Rabbit
Result: No skin irritation
Method: OECD Test Guideline 404
Test substance: yes
Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Non persistent irritation

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 405
Vapours may be irritating to eyes, nose, throat, and lungs.
Based on available data, the classification criteria are not met.

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 405
Vapours may be irritating to eyes, nose, throat, and lungs.
Based on available data, the classification criteria are not met.

|| bis(nonylphenyl)amine:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Test substance: yes
Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Result: May cause sensitisation of susceptible persons.

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Exposure routes: Dermal

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Result: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Exposure routes: Dermal
Result: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

|| bis(nonylphenyl)amine:

Test Method: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative
Method: OECD Test Guideline 406
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Germ cell mutagenicity- Assessment : No data available

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

: Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474
Result: negative

Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: negative

: Method: OECD Test Guideline 476

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474
Result: negative

Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative

bis(nonylphenyl)amine:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Test species: Mouse
Result: negative

Carcinogenicity

Product:

This information is not available.

Carcinogenicity - Assessment : No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 451
negative

Method: OECD Test Guideline 453
negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 451
Result: negative

Method: OECD Test Guideline 453
Result: negative

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

|| bis(nonylphenyl)amine:

This information is not available.

Reproductive toxicity

Product:

Effects on fertility : This information is not available.

Effects on foetal development : This information is not available.

Reproductive toxicity - Assessment : No data available

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Effects on fertility : Method: OECD Test Guideline 421
Result: No adverse effects

Effects on foetal development : Method: OECD Test Guideline 421
Result: negative

Reproductive toxicity - Assessment : No toxicity to reproduction

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 421
Result: No adverse effects

Method: OECD Test Guideline 421
Result: negative

Reproductive toxicity - Assessment : No toxicity to reproduction

|| bis(nonylphenyl)amine:

This information is not available.

STOT - single exposure

Product:

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

No data available

Components:

|| bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

No data available

Components:

|| bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

This information is not available.

Repeated dose toxicity - : No data available
Assessment

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 408

Method: OECD Test Guideline 410

Method: OECD Test Guideline 411

Method: OECD Test Guideline 412
No adverse effect has been observed in chronic toxicity tests.

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 408

Method: OECD Test Guideline 410

Method: OECD Test Guideline 411

Method: OECD Test Guideline 412
No adverse effect has been observed in chronic toxicity tests.

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Aspiration toxicity

Product:

No data available

Components:

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

May be fatal if swallowed and enters airways.

|| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

No aspiration toxicity classification

|| bis(nonylphenyl)amine:

No data available

Further information

Product:

No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Chronic toxicity) : No data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : No data available

Ecotoxicology Assessment
Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Components:

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

|| **lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:**

Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to algae	:	NOEL (algae): >= 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to bacteria	:	NOEL : > 1,93 mg/l Exposure time: 10 min Method: DIN 38 412 Part 8
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

|| **lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:**

Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to algae	:	NOEL (algae): >= 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

|| **bis(nonylphenyl)amine:**

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 4 d Test Type: static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 2 d Test Type: static test Test substance: yes Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 100 mg/l Exposure time: 3 d Test Type: static test Method: OECD Test Guideline 201
Toxicity to bacteria	:	EC50 (activated sludge): > 1.000 mg/l Exposure time: 0,1 d

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : No data available

12.2 Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.

Physico-chemical removability : The product is insoluble and floats on water. May be separated mechanically in waste water plants.

Impact on Sewage Treatment : No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B

bis(nonylphenyl)amine:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not biodegradable
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Product:

Bioaccumulation : No data available

Partition coefficient: n-octanol/water : not determined

Components:

bis(nonylphenyl)amine:

Bioaccumulation : Bioconcentration factor (BCF): 1.584,89

Partition coefficient: n-octanol/water : log Pow: > 7,6

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

12.4 Mobility in soil

Product:

Mobility : Should not be released into the environment.

Components:

bis(nonylphenyl)amine:

Stability in soil : Adsorbs on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

bis(nonylphenyl)amine:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects

Product:

Additional ecological information : Should not be released into the environment.
Do not let product enter drains.

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products.

bis(nonylphenyl)amine:

Additional ecological information : Should not be released into the environment.

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
13 02 06*

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
15 01 10*

SECTION 14: Transport information

14.1 UN number

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.2 Proper shipping name

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.3 Transport hazard class

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.4 Packing group

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.5 Environmental hazards

ADR : Not dangerous goods
RID : Not dangerous goods

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.6 Special precautions for user

Remarks : not required

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : This product is being carried under the scope of MARPOL Annex I

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/13/EC on the limitation of emissions of volatile organic compounds : not required under normal use

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances
Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.
H317 : May cause an allergic skin reaction.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Skin Sens. : Skin sensitisation

Further information

Other information : Changes since the last version are highlighted in the margin.
This version replaces all previous versions.

LUKOIL GENESIS SPECIAL FD 5W-20

Version	Revision Date:	Product code:	Date of last issue: 13.03.2015
2.0	11.07.2016	563115	Date of first issue: 13.03.2015
			Print Date: 07.01.2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.