

Page 1 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PAOIL68 PLUS UV (PL68) 500 ml

Art.: 8FX 351 214-201

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

with UV leak detection

Synthetic refrigerating system lubrication oil for vehicle air conditioners

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Behr Hella Service GmbH, Dr.-Manfred-Behr-Str. 1, D-74523 Schwäbisch Hall Telephone: +49 (0) 7907 9446 483 31, Fax: +49 (0) 7907 9446 483 73

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

+49 228 19240 (D-53113 Bonn, 24 hour)

Telephone number of the company in case of emergencies:

Tel.: +49 (0) 7907 9446 483 31

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Symbols: Not applicable Indications of danger: ---

R-phrases:

S-phrases:

Additions:



Page 2 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Contains

Tris-organo-trithiophosphate

May produce an allergic reaction.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Hydrocarbons can be harmful to water.

Endangerment of potable water possible.

Allergic reaction possible.

SECTION 3: Composition/information on ingredients

Polyolefin

3.1 Substance

n.a.

3.2 Mixture

-	
Registration number (REACH)	
Index	-
EINECS, ELINCS, NLP	-
CAS	-
content %	
Classification according to Directive 67/548/EEC	
Classification according to Regulation (EC) 1272/2008 (CLP)	

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Watering eyes

With long-term contact:

Dermatitis (skin inflammation)

Allergic reaction possible.

Ingestion of large quantities:

Vomiting

Diarrhoea

On vapour formation:

Irritant to mucosa of the nose and throat



Page 3 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Indications for the physician: Symptomatic treatment

Ingestion:

Danger of aspiration

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Dry extinguisher Alcohol resistant foam Water jet spray

Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Fume

Oxides of carbon

Toxic pyrolysis products.

5.3 Advice for firefighters

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid aerosol formation.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.



Page 4 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Observe directions on label and instructions for use. Do not heat to temperatures close to flash point.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Remove possible causes of ignition - do not smoke.

Protect against moisture and store closed.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Protective gloves made of polyvinyl alcohol (EN 374)

Protective PVC gloves (EN 374)

Permeation time (penetration time) in minutes:

> 360

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If fumes build up, use suitable breathing mask. Filter A P 3 (EN 14387), code colour brown, white

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).



Page 5 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Physical state:

Viscous
Colour:

Colour:

Colour:

Yellow
Odour:

Mild

Odour threshold: Not determined pH-value: Not determined

Melting point/freezing point: -63--54 °C (ASTM D 97, Setting point)

Initial boiling point and boiling range:

Not determined

Flash point: >200 °C (ASTM D 93 (Pensky-Martens, closed cup))

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Not determined

Not determined

Not determined

Not determined

Not determined

Density: 0,828-0,843 g/ml (15°C, ASTM D 1298)

Bulk density:

Solubility(ies):

Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not determined

Not determined

Not determined

Not determined

Not determined

Not determined

Viscosity:

30,7-99,6 cSt (40°C)

Viscosity: 5,76-14 cSt (100°C, ASTM D 445)

Explosive properties:

Oxidising properties:

Not determined

Not determined

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.



Page 6 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

10.4 Conditions to avoid

See also section 7. Product is combustible. Open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201 Toxicity/effect Endpoi Value Unit **Organism** Test method Notes nt Acute toxicity, by oral route: n.d.a. Acute toxicity, by dermal n.d.a. route: Acute toxicity, by inhalation: n.d.a. Skin corrosion/irritation: n.d.a. Serious eye n.d.a. damage/irritation: Respiratory or skin n.d.a. sensitisation: Germ cell mutagenicity: n.d.a. Carcinogenicity: n.d.a. Reproductive toxicity: n.d.a. Specific target organ toxicity n.d.a. single exposure (STOT-SE): Specific target organ toxicity n.d.a. repeated exposure (STOT-RE): Aspiration hazard: n.d.a. Respiratory tract irritation: n.d.a. Repeated dose toxicity: n.d.a. Symptoms: n.d.a. Other information: Classification according to calculation procedure.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

PAOIL68 PLUS UV (PL68) 500 ml									
Art.: 8FX 351 214-201									
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Toxicity to fish:							n.d.a.		
Toxicity to daphnia:							n.d.a.		
Toxicity to algae:							n.d.a.		



Page 7 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Persistence and				Mechanical
degradability:				precipitation possible.
Bioaccumulative				Concentration in
potential:				organisms possible.
Mobility in soil:				n.d.a.
Results of PBT and				n.d.a.
vPvB assessment				
Other adverse effects:				n.d.a.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 06 synthetic engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

15 01 01 paper and cardboard packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2013):

LQ (ADR 2009):

n.a.

n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Marine Pollutant:

n.a.

n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es):

n.a.

Packing group:

n.a.

Environmental hazards: Not applicable



Page 8 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

n.a.

For classification and labelling see Section 2.

Observe restrictions:

VOC 1999/13/EC ---

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 1 - 16

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIHAmerican Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)



SERVICE

(GB)

Page 9 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSHNational Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million



Page 10 of 10

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0003

Replaces revision of / Version: 15.05.2009 / 0002

Valid from: 19.01.2011 PDF print date: 10.03.2014

PAOIL68 PLUS UV (PL68) 500 ml Art.: 8FX 351 214-201

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.