



Service Info

LuK RepSet with SAC

Different design of the pressure plates

The LuK RepSet with self-adjusting clutch (SAC) has already been delivered with the standard pressure plate design for many years now (Fig. 1). The most striking features of these pressure plates are the circularly arranged ramps on the clutch housing and the adjustment ring with its radially acting compression springs.

As a result of the continuous further development of our products, the previous SAC pressure plates in some LuK RepSets are being replaced by modified pressure plates (Fig. 2). These versions can be recognized by the riveted adjustment springs and the rampless surface of the clutch housing.

In case of repairs, LuK RepSets with modified pressure plates can be used on all vehicles listed in the catalog without restriction, even where pressure plates of the previous design have been installed.



Fig. 2: Modified self-adjusting pressure plate without ramps with adjustment spring

Note:

All SAC pressure plates must be installed without counterforce and in case of reuse, must also be removed by means of this same procedure. Proper removal/installation is facilitated by the LuK special tool with the Part No.: 400 0237 10. For further information on the SAC, please refer to the LuK brochure "Self-Adjusting Clutch (SAC)".



Fig. 2: Modified self-adjusting pressure plate without ramps with adjustment spring

Please observe the vehicle manufacturer specifications!

You want more? We can help!

Phone: +44 (0) 1432 264 264*

Fax: +44 (0) 1432 375 760

hfd-info@schaeffler.com

www.schaeffler-aftermarket.co.uk

* Calls from within the UK 08457 001100



SCHAEFFLER

REP>XPERT