ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#1/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code: ALE' OO (VERDE) Trades code: EVERTON 63

1.2. Relevant identified uses of the substance or mixture and uses advised against

Hand horn

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Other products (use ConsExpo subcategories or UCN codes)

Uses advised against

Do not use for purposes other than those listed

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

CAS 115-10-6 CEE 603-019-00-8 EINECS 204-065-8

2.1.1 Classification according to Directive 1999/45/EEC:

Classification:

Nonhazardous

Nature of special risks attributed:

None in particular.

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

2.2. Label elements

Labeling according to Directive (EC) No 1999/45:

Provided symbols:

No hazard symbol expected

Attributed risk:

The product does not introduce specific risks.

Precautionary statements:

S9 - Keep container in a well-ventilated place.

S23 - Do not breathe spray.

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#2/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

- S46 If swallowed, seek medical advice immediately and show this container or label.
- S51 Use only in well-ventilated areas.
- S56 Dispose of this material and its container to hazardous or special waste collection point.

WARNINGS:

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn even after use. Keep out of reach of children.

5% by mass of the contents are flammable.

Safety data sheet available for professional user on request

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

No substance to signal.

SECTION4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product).:

Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product).:

Wash immediately and thorougly with running water for at least 10 minutes.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to substances refer to paragraph 11.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#3/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

Extinguishing means to avoid:

Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear suitable gloves (PVC, butyl rubber, neoprene or similar) and protective clothing.

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#4/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

SECTION7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors. See also paragraph 8 below.

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Always store in well ventilated areas.

Store in a cool place, away from sources of heat and `direct exposure of sunlight.

7.3. Specific end use(s)

Private households (= general public = consumers):

- Keep away from heat sources, sparks, open flames
- Do not breathe spray/vapours
- · Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

Public domain (administration, education, entertainment, services, craftsmen):

- Keep away from heat sources, sparks, open flames
- Do not breathe spray/vapours
- Avoid contact with eyes, skin, clothing
- Do not eat, drink or smoke when using
- Do not use in confined and/or limited spaces
- Use at a distance of 20 cm from the surface to be treated to prevent dispersion in the air
- Spray only briefly and take care for a good ventilation after use

SECTION8. Exposure controls/personal protection

8.1. Control parameters

No data available.

8.2. Exposure controls



Appropriate engineering controls:

Private households (= general public = consumers):

Work in a well ventilated place or equipped with ventilation devices. Do not use on hot surfaces or surfaces exposed to sunlight in order to avoid rapid evaporation of the product. Use personal protective equipment (see below).

Public domain (administration, education, entertainment, services, craftsmen):

The use of appropriate technical measures should always take priority over personal protective equipment. Ensure good ventilation in the workplace through effective local aspiration. If these steps are not enough to maintain the concentration of the product below the exposure limit values in the workplace, wear appropriate respiratory protection. Provide a system for eye wash. Before using the product refer to the label for hazard details. During the selection of personal protective equipment, seek appropriate advice from the supplier. Personal protective equipment must comply with regulations in force.

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#5/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

Individual protection measures:

- (a) Eye / face protection Wear safety goggles to EN-166
 - (b) Skin protection
- (i) Hand protection Not needed for normal use.
- (ii) Other Avoid direct contact with the skin Better is to use cotton antistatic clothing
- (c) Respiratory protection Work in a sufficiently ventilated to avoid inhaling the product.
- (d) Thermal hazards No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical and chemical properties | Value | Determination method |
|--|-----------------------------------|----------------------|
| Appearance | liquid gas under pressure | VISUAL |
| Odour | almost odorless | ORGANOLEPTIC |
| Odour threshold | not determined | |
| рН | irrelevant | PH-METER |
| Melting point/freezing point | -100 °C | |
| Initial boiling point and boiling range | -26 °C | |
| Flash point | non-flammable | |
| Evaporation rate | not determined | |
| Flammability (solid, gas) | irrelevant | |
| Upper/lower flammability or explosive limits | non-flammable | |
| Vapour pressure | 5,4 bar | |
| Vapour density | 4,32 at 20 °C (tetrafluoroethane) | |
| Relative density | 1,2 kg/l | |
| Solubility | non-oxidizing | |
| Water solubility | 1.5 g/l (tetrafluoroethane) | |
| Partition coefficient: n-octanol/water | 1.06 (tetrafluoroethane) | |
| Auto-ignition temperature | non-flammable | |
| Decomposition temperature | not determined | |
| Viscosity | 0,21 mPa*s at 25 °C | |
| Explosive properties | irrelevant | |
| Oxidising properties | irrelevant | |
| Container volume | 520 ml | ISO 90-3:2000 |

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#6/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

| Physical and chemical properties | Value | Determination method |
|----------------------------------|---------------|----------------------|
| Product volume | 400 ml | ISO 90-3:2000 |
| Pressure to 20 °C | 5,4 bar | |
| Deformation pressure | 16,5 bar | MANOMETER GAUGE |
| Burst pressure of the container | 18 bar | MANOMETER GAUGE |
| Flash point of liquid phase | non-flammable | |
| Propellent inflammability | non-flammable | |

9.2. Other information

No data available.

SECTION10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 °C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can ignite in contact with oxidants mineral acids, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION11. Toxicological information

11.1. Information on toxicological effects

- (a) acute toxicity: not applicable
- (b) irritation: not applicable
- (c) corrosivity: not applicable
- (d) sensitisation: not applicable
- (e) repeated dose toxicity;: not applicable
- (f) carcinogenicity: not applicable
- (g) mutagenicity: not applicable
- (h) toxicity for reproduction: not applicable

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#7/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

SECTION12. Ecological information

12.1. Toxicity

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 °C can burst.

Recover if possible. Operate according to local or national regulations

SECTION14. Transport information

14.1. UN number

1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

14.2. UN proper shipping name

AEROSOL asphyxiant

14.3. Transport hazard class(es)

Class: 2 Label: 2.2

Tunnel restriction code : E Limited quantities : 1 L

EmS: F-D, S-U

ALE' OO (VERDE)

Issued on 11/23/2010 - Rel. # 1 on 11/23/2010

#8/8

In conformity to Regulation (EC) No 453/2010 of 20 May 2010

14.4. Packing group

--

14.5. Environmental hazards

Product is not environmentally hazardous Marine polluting agent : Not

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions.

The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 96/82/EC (Seveso), annex I, part 2: category 8

Control of Substances Hazardous to Health (COSHH), Regulations 2002

Regulation 2006/1907/EC (REACH), Regulation 2008/1272/EC (CLP), Regulation 2009/790/EC.

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION16. Other information

16.1. Other information

Classification based on data of all mixture components

Main normative references:
Directive 67/548/EEC (29th adaptation)
Directive 1999/45/EC
Directive 2001/60/EC
Regulation 1272/2008/EC
Regulation 2010/453/EC

^{***} This tab annuls and replaces any previous edition.