

# SAFETY DATA SHEET POLYGARD OAT (RED) ANTIFREEZE COOLANT

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	POLYGARD OAT (RED) ANTIFREEZE COOLANT
Product number	16200, 16205, 16210, 16220, 16230, 16321
Internal identification	B16911
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Antifreeze liquid.
Uses advised against	This product is not recommended for any industrial, professional or consumer use other than the identified uses stated above.
1.3. Details of the supplier of the	he safety data sheet
Supplier	
	Miswa Chemicals Ltd
	Caswell Road
	Brackmills
	Northampton
	England NN4 7PW
	T: +44 (0)1604 701111
	F: +44 (0)1604 701120
	SDSAdmin@miswa.com
14 Emorrana / talanhana	
1.4. Emergency telephone nur	
Emergency telephone	T: +44 (0)1604 701111 (Miswa Office Hours Monday - Friday (0900Hrs - 1700Hrs))
SECTION 2: Hazards identification	ation
2.1. Classification of the substa	ance or mixture
Classification (EC 1272/2008)	
Physical hazards	Not Classified
Health hazards	Acute Tox. 4 - H302 STOT RE 2 - H373
Environmental hazards	Not Classified
Classification (67/548/EEC or 1999/45/EC)	Xn;R22.
2.2. Label elements	
Pictogram	

Signal word	Warning
Hazard statements	H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
Precautionary statements	<ul> <li>P260 Do not breathe vapour/ spray.</li> <li>P264 Wash contaminated skin thoroughly after handling.</li> <li>P270 Do not eat, drink or smoke when using this product.</li> <li>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</li> <li>P314 Get medical advice/ attention if you feel unwell.</li> <li>P330 Rinse mouth.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> <li>P102 Keep out of reach of children.</li> </ul>
Containa	

Contains

ETHANEDIOL

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

# SECTION 3: Composition/information on ingredients

3.2. Mixtures			
ETHANEDIOL		60-10	0%
CAS number: 107-21-1	EC number: 203-473-3	REACH registration number: 01-	
		2119456816-28-XXXX	
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302	Xn;R22		
STOT RE 2 - H373			
SODIUM BENZOATE		<	<1%
CAS number: 532-32-1	EC number: 208-534-8	REACH registration number: 01-	
		2119460683-35-XXXX	
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Eye Irrit. 2 - H319	-		
TOLYLTRIAZOLE		<	<1%
CAS number: 29385-43-1	EC number: 249-596-6	REACH registration number: 01-	
		2119979081-35-XXXX	
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302		R36. N;R51/53.	
Eye Irrit. 2 - H319			
Aquatic Chronic 2 - H411			
DISODIUM MONOMOLYBDATE	DIHYDRATE	<	<1%
CAS number: 10102-40-6	EC number: 231-551-7	REACH registration number: 05-	
		2116507364-51-XXXX	
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)	
Not Classified	-	·	

DENATONIUM BENZOATE	<1%
CAS number: 3734-33-6	EC number: 223-095-2
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H332 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) Xn;R20/22. Xi;R36/37/38. R52/53.
The Full Text for all R-Phrase	es and Hazard Statements are Displayed in Section 16.
Composition comments	The data shown are in accordance with the latest EC Directives.
SECTION 4: First aid measu	res
4.1. Description of first aid me	easures
General information	First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Inhalation	Move affected person to fresh air at once. Get medical attention. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Do not induce vomiting. Remove affected person from source of contamination. Get medical attention immediately. If person is fully conscious give 1 cup or 8 ounces (240 ml) of water. If medical advice is delayed and if an adult has swallowed several ounces of chemical, then give 3-4 ounces (1/3-1/2 Cup) (90-120 ml) of hard liquor such as 80 proof whiskey. For children, give proportionally less liquor at a dose of 0.3 ounce (1 1/2 tsp.) (8 ml) liquor for each 10 pounds of body weight, or 2 ml per kg body weight [e.g., 1.2 ounce (2 1/3 tbsp.) for a 40 pound child or 36 ml for an 18 kg child].
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing. Wash contaminated clothing before reuse. Destroy contaminated leather items such as shoes, belts, and watchbands.
Eye contact	Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.
4.2. Most important symptom	is and effects, both acute and delayed
General information	Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.
4.3. Indication of any immedia	ate medical attention and special treatment needed

3/16

### Notes for the doctor

Check section 3.2 to obtain percentage of ethylene glycol in this product, the following is based on 100% ethylene glycol content. If several ounces (60 - 100 ml) of ethylene glycol have been ingested, early administration of ethanol may counter the toxic effects (metabolic acidosis, renal damage). Consider hemodialysis or peritoneal dialysis & thiamine 100 mg plus pyridoxine 50 mg intravenously every 6 hours. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG), di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol (Brent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. If burn is present, treat as any thermal burn, after decontamination. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

#### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from	om the substance or mixture
Specific hazards	Combustible Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.
Hazardous combustion products	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Nitrogen oxides.
5.3. Advice for firefighters	
Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Fight advanced or massive fires from safe distance or protected location. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Do not use water jet as an extinguisher, as this will spread the fire. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Extinguishing waters may present a risk of damage to the environmental, collect and dispose of as hazardous waste, in accordance with local legislation.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsIsolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to<br/>Section 7, Handling, for additional precautionary measures. Use appropriate safety<br/>equipment. For additional information, refer to Section 8, Exposure Controls and Personal<br/>Protection. No smoking, sparks, flames or other sources of ignition near spillage. Avoid<br/>inhalation of vapours and contact with skin and eyes.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning upContain spilled material if possible. Containers with collected spillage must be properly<br/>labelled with correct contents and hazard symbol. Small Spillages: Absorb with materials such<br/>as: Cat litter. Sand. Sawdust. Zorb-all®. Hazorb®. Large spills: Dike area to contain spill.<br/>Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations,<br/>for additional information.

#### 6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health
	hazards. For waste disposal, see Section 13.

#### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Do not swallow. Do not handle broken packages without protective equipment. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid contact with skin and eyes.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs. Keep only in the original container.	
7.3. Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	
SECTION 8: Exposure Controls/personal protection		
8.1. Control parameters		

#### Occupational exposure limits

### ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 52 mg/m<sup>3</sup> 20 ppm Short-term exposure limit (15-minute): WEL 104 mg/m3 40 ppm vapour Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> particulate

### SODIUM BENZOATE

No exposure limit value known.

### TOLYLTRIAZOLE

No exposure limit value known.

### DISODIUM MONOMOLYBDATE DIHYDRATE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup>, as Mo. inhalable dust Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup> inhalable dust as Mo

### DENATONIUM BENZOATE

No exposure limit value known. WEL = Workplace Exposure Limit Sk = Can be absorbed through skin.

Ingredient comments WEL = Workplace Exposure Limits

## ETHANEDIOL (CAS: 107-21-1)

DNEL	Industry - Dermal; Long term systemic effects: 106 mg/kg bw/day Industry - Inhalation; Long term local effects: 35 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 53 mg/kg bw/day Consumer - Inhalation; Long term local effects: 7 mg/m <sup>3</sup> - Fresh water; 10 mg/l - Marine water; 1 mg/l - Sediment (Freshwater); 37 mg/kg sediment dw - Intermittent release; 10 mg/l - Soil; 1.53 mg/kg - STP; 199.5 mg/l - Sediment (Marinewater); 3.7 mg/kg sediment dw
	- Soil; 1.53 mg/kg soil dw
	SODIUM BENZOATE (CAS: 532-32-1)
DNEL	Workers - Inhalation; Long term systemic effects: 3 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 62.5 mg/kg bw/day Workers - Inhalation; Long term local effects: 0.1 mg/m <sup>3</sup> General population - Inhalation; Long term systemic effects: 1.5 mg/m <sup>3</sup> General population - Inhalation; Long term local effects: 0.06 mg/m <sup>3</sup> General population - Dermal; Long term systemic effects: 31.25 mg/kg bw/day General population - Oral; Long term systemic effects: 16.6 mg/kg bw/day
PNEC	<ul> <li>Fresh water; 0.13 mg/l</li> <li>Marine water; 0.013 mg/l</li> <li>Intermittent release; 0.305 mg/l</li> <li>STP; 10 mg/l</li> <li>Sediment (Freshwater); 1.76 mg/kg sediment dw</li> <li>Sediment (Marinewater); 0.176 mg/kg sediment dw</li> <li>Soil; 0.000265 mg/kg soil dw</li> </ul>
	TOLYLTRIAZOLE (CAS: 29385-43-1)
DNEL	Workers - Inhalation; Long term systemic effects: 8.8 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 0.5 mg/kg bw/day General population - Inhalation; Long term systemic effects: 4.4 mg/m <sup>3</sup> General population - Dermal; Long term, Short term systemic effects, Acute: 0.25 mg/kg bw/day

PNEC	- Fresh water; 0.008 mg/l - Marine water; 0.008 mg/l - Intermittent release; 0.086 mg/l - STP; 39.4 mg/l
	- Sediment (Freshwater); 0.0025 mg/kg sediment dw
	- Sediment (Marinewater); 0.0025 mg/kg sediment dw
	- Soil; 0.0024 mg/kg soil dw
DI	ISODIUM MONOMOLYBDATE DIHYDRATE (CAS: 10102-40-6)
DNEL	Workers - Inhalation; Long term systemic effects: 28 mg/m <sup>3</sup>
PNEC	- Fresh water; 32.0 mg/l
	- Marine water; 4.8 mg/l
	- Sediment (Freshwater); 57000 mg/kg sediment dw
	- Sediment (Marinewater); 4995 mg/kg sediment dw
	- Soil; from 29.8 to 474 mg/kg soil dw
	- STP; 54.7 mg/l
	DENATONIUM BENZOATE (CAS: 3734-33-6)
DNEL	Workers - Inhalation; Long term systemic effects: 15.748 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 8.932 mg/kg bw/day
	General population - Inhalation; Long term systemic effects: 3.883 mg/m <sup>3</sup>
	General population - Dermal; Long term systemic effects: 4.466 mg/kg bw/day
	General population - Oral; Long term systemic effects: 2.233 mg/kg bw/day
PNEC	- Fresh water; 0.1 mg/l
PNEC	- Marine water; 0.01 mg/l
PNEC	- Marine water; 0.01 mg/l - Intermittent release; 1 mg/l
PNEC	- Marine water; 0.01 mg/l - Intermittent release; 1 mg/l - STP; 51.158 mg/l
PNEC	<ul> <li>Marine water; 0.01 mg/l</li> <li>Intermittent release; 1 mg/l</li> <li>STP; 51.158 mg/l</li> <li>Sediment (Freshwater); 33.692 mg/kg sediment dw</li> </ul>
PNEC	- Marine water; 0.01 mg/l - Intermittent release; 1 mg/l - STP; 51.158 mg/l

## 8.2. Exposure controls

#### Protective equipment



# Appropriate engineering controls

Eye/face protection

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Use safety glasses (with side shields), consistent with EN 166 or equivalent. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles (goggles consistent with EN 166 or equivalent). If exposure causes eye discomfort, use a full-face respirator.

Hand protection	Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. Use gloves with insulation for thermal protection (EN 407), when needed. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. When handling hot material, protect skin from thermal burns as well as from skin absorption.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not eat, drink or smoke when using this product.
Respiratory protection	Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and Chemical Properties

## 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.	
Colour	Reddish. Pink.	
Odour	Almost odourless. Characteristic.	
рН	pH (diluted solution): 8.0 to 8.6 @ 50% water solution	
Initial boiling point and range	>160°C @ 760 mm Hg	
Flash point	117°C CC (Closed cup).	
Relative density	1.12 to 1.14 @ 20°C	
9.2. Other information		
SECTION 10: Stability and reactivity		

10.1. Reactivity	
Reactivity	Stable at normal ambient temperatures and when used as recommended.
10.2. Chemical stability	·
Stability	Stable at normal ambient temperatures.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Will not polymerise.
10.4. Conditions to avoid	
Conditions to avoid	Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.
10.5. Incompatible materials	
Materials to avoid	Strong acids. Strong oxidising agents. Strong alkalis.
10.6. Hazardous decomposition	on products
Hazardous decomposition products	Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ethers. Alcohols.
SECTION 11: Toxicological in	formation
11.1. Information on toxicolog	ical effects
Toxicological effects	The product is not expected to be toxic to aquatic organisms.
Other health effects	There is no evidence that the product can cause cancer.
Acute toxicity - oral	
Notes (oral LD₅₀)	Harmful if swallowed.
ATE oral (mg/kg)	540.31
Specific target organ toxicity -	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
General information	To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated.
Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. Vapour may irritate respiratory system/lungs.
Ingestion	Harmful: possible risk of irreversible effects if swallowed. Headache. Nausea, vomiting. There may be soreness and redness of the mouth and throat.
Skin contact	Prolonged and frequent contact may cause redness and irritation. Not a skin sensitiser.
Eye contact	May cause eye irritation.
Acute and chronic health hazards	May cause damage to kidneys and liver through prolonged or repeated exposure (oral).
Route of entry	Ingestion.
Medical symptoms	Headache. Nausea, vomiting.

## ETHANEDIOL

Acute toxicity - oral	
Acute toxicity oral (LD <sub>50</sub>	7,712.0
mg/kg)	
Species	Rat
Notes (oral LD∞)	Acute oral toxicity is expected to be moderate in humans eventhough animals test results would suggest a low toxicity. Ingestion of approximately 100ml has caused death in humans. Ingestion may cause nausea, vomiting, abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects and kidney failure.
ATE oral (mg/kg)	500.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	3,501.0
Species	Mouse
ATE dermal (mg/kg)	3,501.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	2.6
Species	Rat
Notes (inhalation LC₅₀)	At room temperature exposure to vapour is minimal due to low volatility. With good ventilation single exposure is not expected to cause adverse effect. If the product is heated or the working area has poor ventilation, vapour/mist may accumulate and cause respiratory irritation and symptoms such as headache and nausea.
Skin corrosion/irritation	
Animal data	Not irritating. Rabbit
Serious eye damage/irritati	on
Serious eye damage/irritation	Not irritating. Rabbit
Respiratory sensitisation	
Respiratory sensitisation	Guinea pig: Not sensitising.
Skin sensitisation	
Skin sensitisation	- Guinea pig: Not sensitising.
Germ cell mutagenicity	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
Carcinogenicity	
Carcinogenicity	The current toxicological kowledge allows to not classify the product as a carcinogen.
Reproductive toxicity	
Reproductive toxicity - fertility	Ingestion of large amounts has been shown to interfere with reproduction in animals.

## Specific target organ toxicity - repeated exposure

STOT - repeated exposure	Observations in humans include: Nystagmus (involuntary eye movement). In animals effects have been reported on the following organs: kidneys and liver. NOAEL 150 mg/kg/day, Oral, Rat
Target organs	Kidneys
Inhalation	At room temperature, exposure to vapor is minimal due to low volatility. With good ventilation, single exposure is not expected to cause adverse effects. If material is heated or areas are poorly ventilated, vapor/mist may accumulate and cause respiratory irritation and symptoms such as headache and nausea.
Ingestion	Oral toxicity is expected to be moderate in humans due to ethylene glycol even though tests with animals show a lower degree of toxicity. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. For Ethylene glycol: Lethal Dose, Human, adult 100 ml LD50, rat, male and female 7,712 mg/kg.
Skin contact	Prolonged skin contact is unlikely to result in absorption of harmful amounts. Repeated skin exposure to large quantities may result in absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn skin may result in absorption of potentially lethal amounts.
Eye contact	May cause temporary eye irritation.
Route of entry	Ingestion.
Target organs	Kidneys Liver
	DISODIUM MONOMOLYBDATE DIHYDRATE
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	2,733.0
Species	Rat
ATE oral (mg/kg)	2,733.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	2,001.0
Species	Rat
ATE dermal (mg/kg)	2,001.0
Skin corrosion/irritation	

Animal data Not irritating.

Serious eye damage/irritation

Serious eye Not irritating. damage/irritation

**Respiratory sensitisation** 

	Respiratory sensitisation	Data lacking.
	Skin sensitisation	
	Skin sensitisation	Not sensitising.
	Germ cell mutagenicity	
	Genotoxicity - in vitro	Negative.
	Genotoxicity - in vivo	Negative.
	Carcinogenicity	
	Carcinogenicity	Based on available data the classification criteria are not met.
	Reproductive toxicity	
	Reproductive toxicity - fertility	Data lacking.
	Specific target organ toxicity - single exposure	
	STOT - single exposure	Based on available data the classification criteria are not met.
	Specific target organ toxicity - repeated exposure	
	STOT - repeated exposure	Data lacking.
	Aspiration hazard	
	Aspiration hazard	Not considered an aspiration hazard.
<b>SECTION 1</b>	2: Ecological Information	
Ecotoxicity	are not c	luct is not expected to be hazardous to the environment. The product components lassified as environmentally hazardous. However, large or frequent spills may have us effects on the environment.
12.1. Toxicit	<u>v</u>	
Toxicity	The proc	luct is not expected to be toxic to aquatic organisms.
		ETHANEDIOL
	Toxicity	Product not classified as dangerous to aquatic organisms.
	Acute toxicity - fish	LC50, 96 hours: 72860 mg/l, Pimephales promelas (Fat-head Minnow)
	Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: > 100 mg/l, Daphnia magna
	Acute toxicity - aquatic plants	EC₅₀, 96 hours: 6500 - 13000 mg/l, Selenastrum capricornutum
	Acute toxicity - microorganisms	EC20, 30 minutes: > 1995 mg/l, Activated sludge
	Chronic toxicity - fish early life stage	NOEC, 7 days: 15380 mg/l, Pimephales promelas (Fat-head Minnow)
	Chronic toxicity - aquatic invertebrates	NOEC, 7 days: 8590 mg/l, Ceriodaphnia Sp.

## DISODIUM MONOMOLYBDATE DIHYDRATE

	Acute toxicity - fish	LC₅₀, 96 hours: 1536-1718 mg/l, Pimephales promelas (Fat-head Minnow)
	Acute toxicity - aquatic invertebrates	LC₅₀, 48 hours: 330.1 mg/l, Daphnia magna
	Acute toxicity - aquatic plants	EC₅₀, Effect on growth., 72 hours: 840 mg/l, Pseudokirchneriella subcapitata
	Acute toxicity - microorganisms	$EC_{50}$ , 3 hours: 216.5 mg/l, as Mo, Activated sludge
12.2. Persiste	ence and degradability	
Persistence a		duct is biodegradable but it must not be discharged into drains without permission authorities. The product is degraded completely by photochemical oxidation.
		ETHANEDIOL
	Persistence and degradability	The product is biodegradable.
	Biodegradation	Water - Degradation (%) 90 - 100%: 10 days Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% biodegradation in OECD test(s) for inherent biodegradability).
		DISODIUM MONOMOLYBDATE DIHYDRATE
	Persistence and degradability	Not applicable.
12.3. Bioaccu	imulative potential	
Bioaccumulat	tive potential The pro	duct does not contain any substances expected to be bioaccumulating.
		ETHANEDIOL
	Bioaccumulative potential	Not potentially bioaccumulative
	Partition coefficient	log Pow: -1.36
		DISODIUM MONOMOLYBDATE DIHYDRATE
	Bioaccumulative potential	Low potential.
12.4. Mobility	n soil	
Mobility	The pro	duct is soluble in water. Volatilization from natural bodies of water or moist soil is not d to be an important fate process.
		ETHANEDIOL
	Mobility	The product is soluble in water. Volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high.
	Adsorption/desorption coefficient	Water - Koc: ~ 1 @ °C
	Henry's law constant	~ 8.05E-09 atm m3/mol @ 25°C

# POLYGARD OAT (RED) ANTIFREEZE COOLANT

## DISODIUM MONOMOLYBDATE DIHYDRATE

Mobility	Mobile in soils.
12.5. Results of PBT and vPv	B assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
	ETHANEDIOL
Results of PBT a assessment	and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.
	DISODIUM MONOMOLYBDATE DIHYDRATE
Results of PBT a assessment	and vPvB PBT assessment does not apply.
12.6. Other adverse effects	
Other adverse effects	Not applicable.
SECTION 13: Disposal consid	Ierations
13.1. Waste treatment method	et
General information	This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.
Disposal methods	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses.
SECTION 14: Transport inform	nation
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
Road transport notes	Not classified.
Rail transport notes	Not classified.
Sea transport notes	Not classified.
Air transport notes	Not classified.
14.1. UN number	
Not applicable.	
14.2. UN proper shipping nam	
Not applicable.	
14.3. Transport hazard class(	es)
No transport warning sign req	uired.

## 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

## Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

### SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Pollution (Special Waste) Regulations 1980 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Introduction to Local Exhaust Ventilation HS(G)37. Approved Classification and Labelling Guide (Sixth edition) L131.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	HS&E Manager.
Revision date	14/02/2017
Revision	6
Supersedes date	29/05/2015
SDS status	Approved.
Risk phrases in full	Not classified. R22 Harmful if swallowed.

Hazard statements in full	H302 Harmful if swallowed.
	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H335 May cause respiratory irritation.
	H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
	H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if
	swallowed.
	H411 Toxic to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.