



SAFETY DATA SHEET TRIPLEWAX SHAKE AND SHINE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TRIPLEWAX SHAKE AND SHINE
Product number TWW100, TWW103, TWW600, TWW603, WMW001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Warning

TRIPLEWAX SHAKE AND SHINE

Hazard statements	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P312 Call a POISON CENTER/ doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Detergent labelling	15 - < 30% aliphatic hydrocarbons, < 5% non-ionic surfactants, < 5% perfumes, Contains Benzisothiazolinone, Methylisothiazolinone
Supplementary precautionary statements	P240 Ground/ bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	10-<30%
CAS number: —	EC number: 927-241-2
REACH registration number: 01-2119471843-32-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	

TRIPLEWAX SHAKE AND SHINE

DIETHANOLAMINE	0.001 - <0.1%
CAS number: 111-42-2	EC number: 203-868-0
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT RE 2 - H373	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move affected person to fresh air at once. Keep affected person away from heat, sparks and flames. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing can take place.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration.
Ingestion	Get medical attention immediately. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person. Keep affected person away from heat, sparks and flames. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention promptly if symptoms occur after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

TRIPLEWAX SHAKE AND SHINE

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritation, burning, lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. The product is highly flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.

Special protective equipment for firefighters Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Use suitable respiratory protection if ventilation is inadequate. Take precautionary measures against static discharges. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13. Stop leak if possible without risk. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Cover large spillages with alcohol-resistant foam.

TRIPLEWAX SHAKE AND SHINE

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Vapours may accumulate on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene procedures should be implemented. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Mechanical ventilation or local exhaust ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Keep only in the original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store away from the following materials: Oxidising materials.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

DIETHANOLAMINE

Long-term exposure limit (8-hour TWA): OES 3 ppm 15 mg/m³

Short-term exposure limit (15-minute): OES

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Use explosion-proof general and local exhaust ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

TRIPLEWAX SHAKE AND SHINE

Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated. When using do not eat, drink or smoke. Contaminated clothing should be placed in a closed container for disposal or decontamination.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type AX.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	White/off-white. or Green.
Odour	Characteristic.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	~100°C @
Flash point	30°C
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.930g/cm ³ @ 20°C
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	>35 cSt @ 40°C

9.2. Other information

Other information	None.
--------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Vapours may form explosive mixtures with air.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not relevant.
---	---------------

TRIPLEWAX SHAKE AND SHINE

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. The product contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Route of entry Inhalation Skin absorption Ingestion. Skin and/or eye contact

Medical symptoms Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Medical considerations Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which has a photochemical ozone creation potential. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute toxicity - fish

LC₅₀, 96 hours: >10 - <30mg/l (HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS) mg/l, Algae

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: >22 - <46mg/l (HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS) mg/l, Daphnia magna

Acute toxicity - aquatic plants

IC₅₀, 72 hours: >1000mg/l (HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS) mg/l, Fish

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

TRIPLEWAX SHAKE AND SHINE

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion. Reuse or recycle products wherever possible.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ETHYL BUTYRATE)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ETHYL BUTYRATE)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ETHYL BUTYRATE)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ETHYL BUTYRATE)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

TRIPLEWAX SHAKE AND SHINE

ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	13/04/2017

TRIPLEWAX SHAKE AND SHINE

Revision	6
Supersedes date	27/09/2016
SDS status	Approved.
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.