

Des.	Pos.	Description
C572	C6	12-pole
C575	A3	4-pole
C576	A3	3-pole
C611	E7	Connector
C615	C4	2-pole
C616	C4	4-pole
C643	C3	3-pole
C666	A2	4-pole
C688	C2	4-pole
C691	D5	Joining sleeve
C694	D5	1-pole
C709	C6	2-pole
C710	C6	2-pole
C714	C6	3-pole
C816	C8	3-pole
C827	C7	2-pole
C860	C5	2-pole
C861	C8	2-pole
C864	C7	3-pole
C865	C8	3-pole
C870	D6	3-pole
C917	C7	2-pole
C2023	C5	2-pole
C2024	C5	2-pole
D521	F8	Reelstar, fan
E510	F5	Node B
E520	F7	Control unit Fan speed roof right
G516	E6	Ground
G541	F7	Ground
L539	C4, B4	Sidewalk lamp Door beh. front axle
L540	C3	Signbox light right
L541	A5	Side mark. lamp Right
L543	A3	Side mark. lamp Right
L571	A6	Direction Indic. side right
L589	A8	Direction Indic. side right
M509	F8	Motor Ventilation fan right
M610	A5	Heat. fan door beh. fr. axle
S528	A3	exterior opening
S575	A4	Pram signal Interior
S579	A3	Ext. pram signal
S580	A3	Ext. open request
S518	A5	Stop req. pass. signal
S620	A7	Pram signal Interior
S621	A7	Stop req. pass. signal
S631	A8	Pram signal Interior
S632	A7	Stop req. pass. signal
S651	A7	Pram signal Interior
S652	A4	Stop req. pass. signal
S688	A6	Pram signal Interior
S689	A4	Stop req. pass. signal
V532	E8	Solenoid valve Heating circuit roof right

**Cable designation**

Cable marking: 100-BN-1+P2/A-4

Cable colour (brown): 1) conductor area, mm<sup>2</sup>

Position reference to component where the cable is connected

1) Unless otherwise stated, conductor area is 0.75 mm<sup>2</sup>

**Additional or optional equipment**

Dotted cable Dotted detail

**Power supply and communication for nodes** are located on a separate drawing.


**Classification acc to S0384**

<C>; -  
<M>; -  
<D>; -  
<L>; 1

**Colour code of electric cables**

BN	Black
BR	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

402827



**16:62-51**

Edition 2

**Nod B**

**Node B**

**Knotenpunkt B**

**Node B**

**Nodo B**

**Noeud B**

**Nodo B**

**Solmu B**

**Węzeł komunikacyjny B**

**Nó B**

**BNS 4.1/BNS 5.1**